



## Cirrus LED Flush Mount C2F Series

### Features

Round floating cloud ceiling mount fixture available in four diameters and can be used in various applications including corridors, baths and public spaces. Fixture mounts to standard junction box (not included).

### Construction

Housing is die-formed of 22-gauge steel. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

### Finish

Back plate is finished in lightning grade white baked glass enamel paint.

### Diffuser

Diffuser is .07" thick vacuum formed smooth white acrylic that is secured by three Phillips head screws.

### Electrical

This unit is direct wired with constant current low voltage electronic LED drivers. The constant current LED driver is rated for up to 36W with a constant voltage of 120 VAC/60 Hz. and is dimmable down to 10% with a 150W 2-wire (Triac) or electronic low voltage (ELV) dimmer. (Fixtures with the larger lumen package utilize (2) LED drivers.)

### Lamping

12W LED module producing 1100 source lumens  
 17W LED module producing 1600 source lumens  
 27W LED module producing 2400 source lumens  
 35W LED module producing 3100 source lumens  
 2700K or 3000K (CCT). Rated for 50,000 Hrs. 90 CRI

### Certification

All fixtures are cETLus listed for damp locations.  
 ENERGY STAR® qualified  
 Title 24/JA8 Compliant

### Options

Battery back-up (add BB to end of model #)

### Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.


**Specifications and dimensions**  
 subject to change without notice.

## Ordering Information:

White	LED	Source Lumens	CCT	DIA.	D
C2F091100L27D1	12W	1100	2700K	9"	3"
C2F091100L30D1	12W	1100	3000K	9"	3"
C2F111600L27D1	17W	1600	2700K	11"	3"
C2F111600L30D1	17W	1600	3000K	11"	3"
C2F142400L27D1	27W	2400	2700K	14"	3"
C2F142400L30D1	27W	2400	3000K	14"	3"
C2F193100L27D1	35W	3100	2700K	19"	3"
C2F193100L30D1	35W	3100	3000K	19"	3"



FLUSH MOUNT



BATTERY BACKUP

LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		



### Wall Dimmer Compatibility Chart

Product can be dimmed to 10% of full scale using a standard two-wire dimmer.

Brand	Model #
Leviton®	6674-POW
Lutron®	CTCL-153P, DVCL-153P