a lora |





P. 1.855.855.8926

CANADA:19054 28TH Avenue Surrey - BC V3Z 6M3 USA: 3035 E. Lone Mountain Rd - Las Vegas, NV, 89081

MARNI PD321212

Not Included) DIFFUSER DETAILS Clear Carved Acrylic Details MATERIAL Aluminum; Clear Carved Acrylic; Iron; LOCATION Dry CANOPY DIMENSIONS D2-7/8" x H1-3/8" REMOTE DRIVER Powered by DR48-119-UNV-RT Remote Driver (Sold		
WATTAGE85WTOTAL LUMENS6150ImDELIVERED LUMENS2400Im*VOLTAGE48V DC InputCOLOR TEMPERATURE3000KCRI (RA)90CRIDIMMABLE DETAILSYes, TRIAC/ELV (Not Included) or 0-10V Dimmer (Optional Not Included)DIFFUSER DETAILSClear Carved Acrylic DryCANOPY DIMENSIONSD2-7/8" x H1-3/8" Powered by DR48-119-UNV-RT Remote Driver (Sold		L145-1/2" x W4-3/8" x H4-3/8"
TOTAL LUMENS61501mDELIVERED LUMENS24001m*VOLTAGE48V DC InputCOLOR TEMPERATURE3000KCRI (RA)90CRIDIMMABLE DETAILSYes, TRIAC/ELV (Not Included) or 0-10V Dimmer (Optiona Not Included)DIFFUSER DETAILSClear Carved Acrylic DetAILSMATERIAL LOCATIONAluminum; Clear Carved Acrylic; Iron;LOCATION DIMENSIONSD2-7/8" x H1-3/8" Powered by DR48-119-UNV-RT Remote Driver (Sold	LIGHT SOURCE	LED with Remote Driver
DELIVERED LUMENS2400Im*VOLTAGE48V DC InputCOLOR TEMPERATURE3000KCRI (RA)90CRIDIMMABLEYes, TRIAC/ELV (Not Included) or 0-10V Dimmer (Optional Not Included)DIFFUSER DETAILSClear Carved Acrylic Darved Acrylic; Iron;LOCATIONDryCANOPY DIMENSIONSD2-7/8" x H1-3/8" Powered by DR48-119-UNV-RT Remote Driver (Sold	WATTAGE	85W
LUMENSVOLTAGE48V DC InputCOLOR TEMPERATURE3000KCRI (RA)90CRIDIMMABLE DETAILSYes, TRIAC/ELV (Not Included) or 0-10V Dimmer (Optional Not Included)DIFFUSER DETAILSClear Carved Acrylic Clear Carved Acrylic; Iron;MATERIAL LOCATIONAluminum; Clear Carved Acrylic; Iron;LOCATION DIMENSIONSD2-7/8" x H1-3/8" Powered by DR48-119-UNV-RT Remote Driver (Sold	TOTAL LUMENS	6150lm
COLOR TEMPERATURE3000KCRI (RA)90CRIDIMMABLEYes, TRIAC/ELV (Not Included) or 0-10V Dimmer (Optional Not Included)DIFFUSER DETAILSClear Carved Acrylic Clear Carved Acrylic; Iron;LOCATIONDryCANOPY DIMENSIONSD2-7/8" x H1-3/8" Powered by DR48-119-UNV-RT Remote Driver (Sold		2400lm*
TEMPERATURE CRI (RA) 90CRI DIMMABLE Yes, TRIAC/ELV (Not Included) or 0-10V Dimmer (Optional Not Included) DIFFUSER Clear Carved Acrylic DETAILS Clear Carved Acrylic; Iron; MATERIAL Aluminum; Clear Carved Acrylic; Iron; LOCATION Dry CANOPY D2-7/8" x H1-3/8" DIMENSIONS Powered by DR48-119-UNV-RT Remote Driver (Sold	VOLTAGE	48V DC Input
DIMMABLE Yes, TRIAC/ELV (Not Included) or 0-10V Dimmer (Optional Not Included) DIFFUSER Clear Carved Acrylic DETAILS Clear Carved Acrylic; Iron; MATERIAL Aluminum; Clear Carved Acrylic; Iron; LOCATION Dry CANOPY D2-7/8" x H1-3/8" DIMENSIONS Powered by DR48-119-UNV-RT Remote Driver (Sold		3000K
Not Included) DIFFUSER DETAILS Clear Carved Acrylic Clear Carved Acrylic; Iron; MATERIAL Aluminum; Clear Carved Acrylic; Iron; LOCATION Dry CANOPY DIMENSIONS D2-7/8" x H1-3/8" REMOTE DRIVER Powered by DR48-119-UNV-RT Remote Driver (Sold	CRI (RA)	90CRI
DETAILS Aluminum; Clear Carved Acrylic; Iron; LOCATION Dry CANOPY D2-7/8" x H1-3/8" DIMENSIONS Powered by DR48-119-UNV-RT Remote Driver (Sold	DIMMABLE	Yes, TRIAC/ELV (Not Included) or 0-10V Dimmer (Optional, Not Included)
LOCATION Dry CANOPY D2-7/8" x H1-3/8" DIMENSIONS REMOTE DRIVER Powered by DR48-119-UNV-RT Remote Driver (Sold		Clear Carved Acrylic
CANOPY D2-7/8" x H1-3/8" DIMENSIONS REMOTE DRIVER Powered by DR48-119-UNV-RT Remote Driver (Sold	MATERIAL	Aluminum; Clear Carved Acrylic; Iron;
DIMENSIONS REMOTE DRIVER Powered by DR48-119-UNV-RT Remote Driver (Sold	LOCATION	Dry
		D2-7/8" x H1-3/8"
Separately)	REMOTE DRIVER	Powered by DR48-119-UNV-RT Remote Driver (Sold Separately)
BRAND Alora	BRAND	Alora

[D - Diameter, L - Length, W - Width, H - Height, E - Extension]

AVAILABLE FINISHES:




PD321212PN Polished Nickel


*For complete warranty terms, please visit: www.aloralighting.com/warranty



REMOTE DRIVER DR48-119-UNV-RT

PROJECT







SPECIFICATION DETAILS

* For custom options, consult factory for details.

Fixture Dimensions	L8-3/4" x W3-3/4" x H1-5/8"
Wattage	120W
Voltage	120-277V
Output	48V DC, 2.5A
Power Factor	≥0.95
THD	<10%
Dimming	100% - 10%, TRIAC or ELV Dimmer (Not Included) or 100% - 10% 0-10V Dimmer (Optional, Not Included)
Certification	cULus, FCC, RoHS
Location	Damp
Weight	3 LBS
Warranty	5 Years
Mounting Orientation	Max 30ft from fixture with 18AWG (See Illustration Sh

Mounting Orientation

Max 30ft from fixture with 18AWG (See Illustration Sheet for more details)



19054 28TH AVENUE SURREY - BC V3Z 6M3 CANADA

COMMENT



WWW.ALORALIGHTING.COM