



BOBBI 10 / 12

FLUSH MOUNT CEILING

location:
DAMP

SPECIFICATIONS:

DESCRIPTION

Flush-mounted round ceiling luminaires, featuring handcrafted glass.
Two sizes available.

LAMPING

Standard: 60W A19 120V incandescent, suitable for dimming, not included.

CFL: 13W 4-Pin CFL with non-dimming electronic ballast. 120V, lamp not included.

GU24 CFL: Self-ballasted GU24 lampholders. 13W max, 120V, lamp not included.

LED: 10W GU24 LED Lamp 120V, dimmable, included.

Consult factory for other CFL configurations., *CFL lamps not included.*

DIFFUSER

Handcrafted glass diffuser is available in Marble decor.

Bobbi 10 #9111: 10" Dia. x 4.25" H

Bobbi 12 #9110: 12" Dia. x 5.25" H

CONSTRUCTION

Glass diffuser is secured to fitter with three set screws.

Stamped aluminum fitter is powder coated white.

MOUNTING


Installs directly to a 4" octagonal outlet box, centered on fixture.

90°C supply wire required for incandescent lamping.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).

Bobbi 10: #9111




DECOR	LAMP OPTIONS	OPTIONS
911110C 10.0" Dia. Opal Cut	(blank) 1x 60W A19 Incan	LW Low Wattage labeling
911152C 10.0" Dia. Marble	D1 1x 13W Quad 120V	
	GU24 1x 13W GU24 120V	
	LED 1x 10W LED 120V, dimmable	

MARBLE



Bobbi 12: #9110



DECOR	LAMP OPTIONS	OPTIONS
911010C 12.0" Dia. Opal Cut	(blank) 2x 60W A19 Incan	LW Low Wattage labeling
911052C 12.0" Dia. Marble	D2 2x 13W Quad 120V	
	GU24 2x 13W GU24 120V	
	LED 2x 10W LED 120V, dimmable	

Ex. 911052C

Bobbi 12 Ceiling w/ Marble Glass

LED 120V PENDANTS:

- Internal driver integrated in the lamp, GU24 base
- Total power of only 10 watts
- Dimmable with a standard dimmer
- Rated life: 30,000 hours
- Frosted acrylic diffuser
- 800 lumens
- CCT: 2800° Kelvin
- CRI: 80+

Project Information:

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 6/15