



## FELIX

12V MINI PENDANTS

location:  
**DRY**

### SPECIFICATIONS:

#### DESCRIPTION

Low voltage mini pendant with Modern Aluminum Shade and Alzak Reflector.

#### LAMPING

**LED:** 10W Integrated source, dimmable, 85+ CRI, 2800°K CCT, 800 lumens, 30,000 hours.

#### SHADE

Shade shall be made of brushed Aluminum or Bronze powder coat. 7.875" Dia. x 10.75" H

#### REFLECTOR

Low glare inner reflector is of Aluminum Alzak, Silver is for Satin Nickel finish and light Copper is for Bronze finish.

#### CORD

Standard cord is 10' field-adjustable coaxial type with teflon jacket. Jacket tint coordinates with metal finish.

#### STANDARD PENDANT


Mini pendant comes complete with flat-style canopy and LED driver.

#### METAL FINISH

Glass retainer hardware and canopies are finished in either Bronze or Satin Nickel.

#### LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



FELIX SHOWN IN SATIN NICKEL & BRONZE

**For ordering information, see next page**

All dimensions provided are nominal.  
Allowance must be made for dimensional tolerance in handcrafted glasses.

**REV 7/15**



# FELIX

12V MINI PENDANTS


## ORDERING:

CONNECTION	SHADE OPTION	LAMP OPTIONS	METAL FINISH
Pendant Fixtures	<b>FELIX</b> Felix	<b>LED</b> 10W LED	<b>BR</b> Bronze
<b>1XT</b> Flat Canopy			<b>SN</b> Satin Nickel

**Ex. 1XT-FELIX-LED-SN**  
Felix LED Pendant, Satin Nickel Finish

## FIXED PENDANT OPTIONS:

### 1XT 1 Light Pendant, Flat Canopy



- Suitable for use on sloped ceilings
- 1x electronic dimmable LED driver, fits partially in junction box
- Installs to standard 4" octagonal junction box
- Bronze or Satin Nickel metal finishes

### 12V LED MINI PENDANT:

- LED driver is located in canopy for optimal performance
- Total power of 10 watts
- 800 lumens
- Rated life: 30,000 hours
- CCT: 2800° Kelvin
- CRI: 85+
- Dimmable (ELV dimmer is recommended)
- Consult factory for 0-10V dimming option.

### Project Information: