

LASSO

MINI SCONCES WALL

location:

SPECIFICATIONS:

DESCRIPTION

Wall-mounted sconce featuring one handcrafted glass.

LAMPING

Standard: 40W Low-pressure G9 Halogen 120V lamp, included. Suitable for use in an open fixture. Dimmable with standard incandescent dimmer.

LED: 5W LED Replaceable source 120V, dimmable, included.

DIFFUSER

Shade shall be handcrafted glass of various decors. Diameter of 4.75" and height of 3.0"

CONSTRUCTION

Fixture utilizes metal arm assembly with stamped steel canopy and faceplate (5" Circle or Square), with plated finish.

METAL FINISH


Fixture shall be finished in Bronze, Chrome or Satin Nickel.


MOUNTING

Installs directly to a 4" octagonal outlet box. Wall-mount only. Designed for uplighting, but may also be oriented downward.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).





ORDERING:

FIXTURE	- (ILASS OPTIONS	- METAL FINISH		- METAL FINISH -		OPTIONS	
1SW Sconce	561	207 Opal Matte	(blank)	40W G9 Hal	BR	Bronze	SQ Squ	are
	561	2GD Gold Glitter	LED	5W LED 120V,	CR	Chrome	Can	ору
	561	2GL Glitter		dimmable	SN	Satin Nickel		

Ex. 1SW-5612GL-SN

Lasso Mini Sconce w/ Glitter Glass, Satin Nickel Finish

Project li	nformation:
------------	-------------



LASSO SHOWN IN GLITTER (5612GL) IN CHROME FINISH & GOLD GLITTER (5612GD)

561207 OPAL MATTE



LED SCONCES:

- Total power of only 5 watts
- · Dimmable with a standard dimmer
- Rated life: 25,000 hours
- 450 lumens
- CCT: 3000° Kelvin
- CRI: 80+

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 7/15