

# SW PAHU 4

**VANITIES WALL** 

location:

### **SPECIFICATIONS:**

#### **DESCRIPTION**

2-4 light vanity luminaires featuring handcrafted glass. Multilight version of 1SW Pahu 4 sconce.

#### **LAMPING**

**Standard:** 40W Low-pressure G9 Halogen 120V lamp, included. Suitable for use in an open fixture. Dimmable with standard incandescent dimmer.

LED: 5W LED Replaceable source 120V, dimmable, included.

#### **DIFFUSER**

Shade shall be handcrafted double glass of various decors. Outer diameter of 4.0" and height of 7.0", spaced 7.875" apart on center.

#### CONSTRUCTION

Fixture utilizes metal arm assembly and stamped steel body, with plated finish. Decorative finials can be removed for downlighting applications. Decorative outlet box cover optional when not required.

#### **METAL FINISH**

Fixture shall be finished in Bronze, Chrome or Satin Nickel.

#### **MOUNTING**

Installs directly to a 4" octagonal outlet box, with 1.75" left or right offset. Canopy allows direct wiring without outlet box, where armored cable or non-metallic sheathed cable is employed, and the decorative outlet box cover is not required. Orient upward or downward, wall-mount only.

#### **LABELS**

UL or ETL Listed. Suitable for Damp Locations (interior use only).



PAHU 4 SHOWN IN CLEAR/OPAL (C44007) WITH SQUARE CANOPY



#### For ordering information, see next page

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

**REV 10/14** 



Pahu 4 3-Light Vanity w/ Trans. Armagnac/Opal Glass,

# SW PAHU 4

# **VANITIES WALL**

# **ORDERING:**

Satin Nickel Finish

FIXTURE	GLASS OPTIONS	- METAL FINISH	- METAL FINISH - OPTIONS
2SW 2 Light Vanity	A44007 Trans. Amethyst/Opal	(blank) 40W G9 Hal	BR Bronze SQ Square
3SW 3 Light Vanity	<b>C44007</b> Clear/Opal	<b>LED</b> 5W LED 120V,	CR Chrome Canopy
4SW 4 Light Vanity	G44007 Trans. Armagnac/Opal	dimmable	SN Satin Nickel
	L44007 Trans. Olive/Opal		
	\$44007 Trans. Smoke/Opal		
	Y44007 Trans. Gold/Opal		

# 





# LED SCONCES:

- Total power of only 5 watts
- Dimmable with a standard dimmer
- Rated life: 25,000 hours
- 450 lumens
- CCT: 3000° Kelvin
- CRI: 80+

Canopy allows direct wiring without outlet box, where
armored cable or non-metallic sheathed cable is
employed, and the decorative outlet box cover is not
$required. \ Orient \ upward \ or \ downward, \ wall-mount \ only.$

4SW: 30.375"L

Project Information:		