



1 W Z R I S E

MINI SCONCES WALL

location:
DAMP

SPECIFICATIONS:

DESCRIPTION

Wall-mounted sconce featuring one handcrafted glass.

LAMPING

Standard: 60W A19 120V incandescent, suitable for dimming.

GU-24 CFL: Self-ballasted GU-24 lampholders. 13W max, 120V. lamps not included.

LED: 10W GU24 LED Lamp 120V, dimmable, included.

DIFFUSER

Shade shall be handcrafted Opal Matte glass.

3.5" x 3.5" x 4.75" H

CONSTRUCTION

Fixture utilizes die-cast arm assembly and stamped steel canopy (4.75" H), with plated metal finish.

METAL FINISH

Fixture shall be finished in Bronze, Chrome or Satin Nickel.

MOUNTING

Installs directly to a 4" octagonal outlet box.


Orient upward or downward, wall-mount only.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



RISE SHOWN IN OPAL MATTE (449807)



ORDERING:

FIXTURE	-	GLASS OPTIONS	-	LAMPING OPTIONS	-	METAL FINISH
1WZ Sconce		449807 Opal Matte		(blank) 60W A19 Incan GU24 13W GU24 120V LED 10W LED 120V, dimmable		BR Bronze CR Chrome SN Satin Nickel

Ex. 1WZ-449807-SN

Rise Mini Sconce w/ Opal Matte Glass,
Satin Nickel Finish

LED SCONCES:

- Internal driver integrated in the lamp, GU24 base
- Total power of only 10 watts
- Dimmable with a standard dimmer
- Rated life: 30,000 hours
- Frosted acrylic diffuser
- 800 lumens
- CCT: 2800° Kelvin
- CRI: 80+

Project Information:

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 10/14