



# TERRA

12V MINI PENDANTS

location:  
**DRY**

## SPECIFICATIONS:

### DESCRIPTION

Low voltage LED mini pendant with handcrafted clear glass and clear crystals.

### LAMPING

**LED:** 6W Integrated source, dimmable, 85+ CRI, 2800°K CCT, 450 lumens, 30,000 hours.

### DIFFUSER

Shade shall be made of handcrafted glass in Clear decor. 8" Dia. x 7" H

### CORD

Standard cord is 10' field-adjustable coaxial type with teflon jacket and decorative sleeve at the socketholder. Jacket tint coordinates with metal finish.

### STANDARD PENDANT

Mini pendant comes complete with flat-style canopy.

### METAL FINISH


Glass retainer hardware and canopies are finished in Satin Nickel.

### LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



CLEAR CRYSTALS



**For ordering information, see next page**

All dimensions provided are nominal.  
Allowance must be made for dimensional tolerance in handcrafted glasses.

**REV 3/16**



# TERRA

12V MINI PENDANTS


## ORDERING:

CONNECTION	GLASS OPTIONS	LAMP OPTIONS	METAL FINISH
Pendant Fixtures	<b>TERRACL</b> Clear Crystals	<b>LED 6W LED</b>	<b>SN</b> Satin Nickel
<b>1XT</b> Flat Canopy			

**Ex. 1XT-TERRACL-LED-SN**  
 Terra LED Pendant, Clear Crystals,  
 Satin Nickel Finish

## FIXED PENDANT OPTION:

### 1XT 1 Light Pendant, Flat Canopy



- Suitable for use on sloped ceilings
- 1x electronic 60W dimmable 120V transformer, fits partially in junction box
- Installs to standard 4" octagonal junction box
- Bronze or Satin Nickel metal finishes

### LED 12V MINI PENDANTS:

- LED driver is located in canopy for optimal performance
- Total power of 6 watts
- 450 lumens
- Rated life: 30,000 hours
- CCT: 2800° Kelvin
- CRI: 85+
- Dimmable (ELV dimming is recommended)
- Consult factory for 0-10V dimming option.

### Project Information: