



WANDA 12

12V MINI PENDANTS

location:
DRY

SPECIFICATIONS:

DESCRIPTION

Low voltage mini pendant with handcrafted glass.

LAMPING

LED: 6W Integrated source, dimmable, 85+ CRI, 2800°K CCT, 450 lumens, 30,000 hours.

DIFFUSER

Shade shall be made of handcrafted glass in various decors. 2.25" Dia. x 12" H

CORD

Standard cord is 10' field-adjustable coaxial type with teflon jacket and decorative sleeve at the socketholder. Jacket tint coordinates with metal finish.

STANDARD PENDANT

Mini pendant comes complete with flat-style canopy.

METAL FINISH


Glass retainer hardware and canopies are finished in Satin Nickel.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



WANDA 12 SHOWN IN LATTE BUBBLE (WAND12LT) & PLUM BUBBLE (WAND12PL)



WAND12BL
BLUE BUBBLE

WAND12CL
CLEAR BUBBLE

WAND12GD
GOLD BUBBLE

WAND12MS
MOSS BUBBLE



For ordering information, see next page

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 7/15



WANDA 12

12V MINI PENDANTS


ORDERING:

CONNECTION	GLASS OPTIONS	LAMP OPTIONS	METAL FINISH
Pendant Fixtures	WAND12BL Blue Bubble	LED 6W LED	SN Satin Nickel
1XT Flat Canopy	WAND12CL Clear Bubble		
	WAND12GD Gold Bubble		
	WAND12LT Latte Bubble		
	WAND12MS Moss Bubble		
	WAND12PL Plum Bubble		

Ex. 1XT-WAND12GD-LED-SN
 Wanda LED Pendant, Gold Bubble Glass,
 Satin Nickel Finish

FIXED PENDANT OPTIONS:

1XT 1 Light Pendant, Flat Canopy



- Suitable for use on sloped ceilings
- 1x electronic dimmable LED driver, fits partially in junction box
- Installs to standard 4" octagonal junction box
- Satin Nickel metal finish

12V LED MINI PENDANT:

- LED driver is located in canopy for optimal performance
- Total power of 6 watts
- 450 lumens
- Rated life: 30,000 hours
- CCT: 2800° Kelvin
- CRI: 85+
- Dimmable (ELV dimming is recommended)
- Consult factory for 0-10V dimming option.

Project Information: