



# PACO 12

FLUSH MOUNT CEILING

location:  
**DAMP**

## SPECIFICATIONS:

### DESCRIPTION

Flush-mounted ceiling fixture, featuring fused 3-piece glass diffuser.

### LAMPING

**Halogen:** 40W low-pressure G9 Halogen 120V lamps, included.

**LED:** 16W Integrated source, 120V, dimmable, 85+ CRI, 3000°K CCT, 1600 lumens, 30,000 hours, included.

### DIFFUSER

Handcrafted glass diffuser in Opal Glossy with clear or smoke stone trim.  
12" Dia. x 3" H

### CONSTRUCTION


Stamped aluminum fitter is powder coated white.

### MOUNTING

Installs directly to a 4" octagonal outlet box, centered on fixture.  
90°C supply wire required for incandescent lamping.

### LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



OPAL/CLEAR STONE (PACO12CLC)

PACO12SMC  
OPAL/SMOKE STONE



## ORDERING:

| FIXTURE/DECOR                       | LAMP OPTIONS                     |
|-------------------------------------|----------------------------------|
| PACO12CLC 12" Dia. Opal/Clear Stone | HAL 2x40W G9 Hal                 |
| PACO12SMC 12" Dia. Opal/Smoke Stone | LED 16W LED 120V,<br>1500 lumens |

**Ex. PACO12CLC-LED**  
Paco 12 Ceiling, Opal/Clear Stone Shade

### Project Information:

All dimensions provided are nominal.  
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 3/17