


LED Steplight

2.5" Width

SS3008-SM

FEATURES

- Integral 120V input driver
- 1- 2.5W Cree XT-E LEDs, 700mA
- 2700°K ±50°K, 90 CRI, 120 lm
- 3W total consumption
- Incandescent step dimming
- Junction box mounts vertically
- Diecast aluminum
- 2½" w x 4¾" h x 8"p, ADA
- Solite Lens
- UL /C-UL Listed for wet location



FINISHES

- Bronze- BZ
- Silver Metallic- SM
- White- WT

Project Notes

1 - 2.5W Cree XT-E LEDs

700mA, 2,700°k ±50k, 90 CRI, 120lm

Integral 120V input driver

- | | | |
|-------------|-----------------|---------------------------|
| • SS3008-BZ | Bronze | 2½" w x 4½" h x ¼" p, ADA |
| • SS3008-SM | Silver Metallic | 2½" w x 4½" h x ¼" p, ADA |
| • SS3008-WT | White | 2½" w x 4½" h x ¼" p, ADA |

Mounting

- Step- and wall-mount applications
- Fits in standard single-switch box, and a 2" x 3" handy box



A Division of Troy-CSL

14508 Nelson Avenue City of Industry, CA 91744 Tel 626-336-4511 Fax 626-336-4266 www.cslighting.com

Rev. 0916