

# CRYST RAMA

LIGHTING THE WAY FOR SIXTY YEARS

### ASSEMBLY INSTRUCTION MODEL #FIO-A9104-GA-CL





All electrical components must be installed by a licensed electrician in accordance with the National Electric Code and the appropriate local electrical codes.

M

c () Intertek

You will need 4–Candelabra 40 Watts Recommended 60 Watts Max USE LED BULBS FOR EXTENDED USE

#### How to Install:

- 1. Have the fixture wire pass through the Center Rod (4), and then attach the Center Rod to the Bottom Frame (5).
- Feed the fixture wire through the Top Cover (3), Top Ring (2), and Loop (1). Then hang Crystal Strand (A) to the Top Cover (3) as per illustration.
- 3. Place the Top Ring (2) over the Top Cover (3), then secure it by turning the Loop (1) until tight.
- The canopy of the fixture can now be mounted to the ceiling by following instruction **Drawing 2**.
- 5. Install the Bulb (8) to the Socket (7).
- Hook the Bottom of Crystal Strand (A) to the Bottom Frame
  (5).

#### Clear Bead Sets:

A. 16 Sets.

(8)10mm + (9)12mm + (9)14mm + (7)18mm

#### Bulb replacement:


1. Install the Bulb (8) into the Socket (7).

WARNING: This product can expose you to lead, which is known to the state of california to cause cancer and / or birth defects or reproductive harm. For more information go to www.P65warnings. ca.gov

# CRYST®RAMA

LIGHTING THE WAY FOR SIXTY YEARS

# ASSEMBLY INSTRUCTION MODEL #FIO-A9104-GA-CL



## Part Number

- A. (1) Mounting Hardware
- B. (1) Canopy; w5"x h0.75"( XFW9104GACAN5IN)
- C. (1) Collar Ring
- D. (1) Collar Loop
- E. (2) Link
- F. (1) Chain ; w4.2mm (XFW9104GACHA4.2MM)
- G. (1) Loop
- H. (1) Top Ring
- I. (1) Top Cover
- J. (1) Central Rod; w0.46"x h21.26" (XFW9104GAR0D21.26IN)
- K. (1) Bottom Frame
- L. (4) Socket (H2")