

Job Name:

Job Type:

Quantity:

PRODUCT DESCRIPTION

A central, cylinder diffuser of opal white acrylic diffuses LED lighting within a cavity of thin ribbed glass of various lengths. Both imaginative and functional, the bright pendants encase an additional down light recessed within a Naturally Aged Brass or Matte Black housing casting light downward.

MEASUREMENTS

DIMENSION MAX OAH CANOPY HANGING WEIGHT

: 1.5" L x 1.5" W x 11" H : 133.25" OAH : 4.75" W x 1.75" H x 4.75" L GHT : 2 lb : : 120-277V : (00 Bated (450 Dol))

LAMPING

Contemporary

Lighting™

 INPUT VOLTAGE
 : 120-277V

 LUMENS
 : 600 Rated (450 Del.)

 BULB
 : 1 x 7.5W LED PCB Integrated , 8W Total

 BULB INCLUDED
 : (Integrated)

 DIMMABLE
 : Universal 3-in-1

 CRI
 : 90 CRI

 COLOR_TEMP
 : 3000K

FINISHES OPTION

Black Natural Aged Brass

GLASS Clear Ribbed 144

MATERIAL Steel, Aluminum, Glass

RATINGS CETLus Dry Location



ADDITIONAL RATED LIFE 35000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.

$\overline{\Box}$	$\overline{2}$

WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER 4200 SHIRLEY DR. I ATLANTA, GA 30336

P. 626.956.4200 | F. 626.956.4225 | et2online.com