Quantity:



PRODUCT DESCRIPTION

Squares of Satin White glass are supported by flat Polished Chrome end caps with an extruded aluminum frame. Housed on the backside of the LED vanity light is a device to select from 5 color temperatures: 2700k-3000k-3500k-4000k-5000k. A dual mounting backplate allows for the fixture to seamlessly install to a switch box making the glass appear as if floating on the wall. An additional mounting bracket and cover plate is included in the packaging to accommodate larger junction boxes. Enhancing these features with a range voltage 120-277V input, makes this heavy hitting note land squarely into specification requests as well as the home improvement

Contemporary

Lighting™

do-it-yourselfer.

MEASUREMENTS	
DIMENSION	: 48" L 5" H x 3.25" Ext
BACK PLATE	: 5" W x 5" H x 2.25" HCO
HANGING WEIGHT	: 6.65 lb
LAMPING	
INPUT VOLTAGE	: 120-277V
LUMENS	: 3,370 Rated (2,700 Del.)
BULB	: 1 x 40W LED PCB Integrate

HANGING WEIGHT	: 6.65 ID
LAMPING	
INPUT VOLTAGE	: 120-277V
LUMENS	: 3,370 Rated (2,700 Del.)
BULB	: 1 x 40W LED PCB Integrated , 40W Total
BULB INCLUDED	: (Integrated)
DIMMABLE	: ELV or Triac
CRI	: 90 CRI
COLOR_TEMP	: 27-30-35-40-50K
LIGHTING_DIRECTIO	N : Omni

FINISHES OPTION

Polished Chrome

GLASS White 01

MATERIAL Aluminum + Glass

RATINGS cETLus Damp Location



ADDITIONAL INSTALL UP/DOWN: Horiz/Vert RATED LIFE 50000 Hours **OPERATING TEMPERATURE:** -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.

E 12

WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER 4200 SHIRLEY DR. I ATLANTA, GA 30336

P. 626.956.4200 | F. 626.956.4225 | et2online.com