

## Product Specifications - E24365-09PC

Job Name:	Job Type:
Quantity:	Comments



## E24365-09PC

**Candela LED Pendant** 

**Finish** 

Polished Chrome

Glass/Shade Frost White

**Product Category** 

Multi-Tier Chandelier

Lamping

Lamping	
Number of Bulbs	36
Light Type	LED
Bulb Type	PCB
Max Bulb Wattage	1.2
Max Fixture Wattage	43.2
Rated Life	
Rated Lumens	±3,024
Color Temp	3000K
Bulb(s)	Integrated
Light Up/Down	N/A
Beam Spread	N/A
CRI	80+
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Yes

weasu	rements
Width	

incasul cilicilis	
Width	32.75"
Height	12.75"
Length	32.75"
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	15.75"
Max Overall Height	135.75"
Hanging Weight	6.10 lbs
Height Adjustable	Yes
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

## Chinning

Snipping	
Carton Weight	8.70 lbs
Carton Width	37"
Carton Height	12"
Carton Length	38"
Carton Cubic Feet	9.74
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Oversize

Certification

_		
-c	11111/2	olonte
_4	Juive	ii ei i i

Safety Rating	Dry	UPC Code	845094079002	Incandescent Watts	N/A
Energy Star	No	Shades Included	N/A	Fluorescent Watts	N/A
CA Title 24	No	Crystals Included	N/A		
CA Title 20	No	Diffuser Included	N/A		
ADA	No	Conversion Kit	N/A		
Dark Sky	N/A	Material	N/A		

Maxim Lighting International and all designs, logos and images © 2016 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.