SURFACE STEP LIGHTS **SL-07 SERIES**

YPE

SPECIFICATIONS

CONSTRUCTION: Cast aluminum, cast brass or 316 Stainless Steel "Hockey Puck" style LENS: Sand blasted tempered flat glass

LAMP SUPPLIED: 18w S8 #1141; 1200 hours average rating (25w max) LAMP SUPPLIED -MR8 MODELS: 20w MR8 FL; 2000 hours average rating (20w max)

LAMP OPTIONS: We recommend 10,000 hours average rating Xenon (-X) or Halogen (-H) or 2.2w 50,000 hours average rating OMNI-2 LED

SOCKET: Single contact bayonet, brass nickel plated lamp socket screw shell (Ba15s); double contact bayonet base (Ba15d) for 120v; both with 200°C silicone lead wires SOCKET -MR8 MODELS: High temp ceramic GU5.3 bi-pin with 250°C silicone lead wires

WIRING: Black 5 foot 18/2 zip cord from base of fixture (12v only) For 25 foot 16/2 fixture lead wire add -25F to catalog number. 120v Standard wiring

CONNECTION: FA-05 Quick Connector (not supplied) from fixture to main cable (12/2, 10/2 or 8/2 only) 12v only

MOUNTING: Back plate and hardware supplied

FINISH: Aluminum - Black texture polyester powder coat. Optional finishes available Brass - Unfinished brass. Optional finishes available Stainless Steel - Brushed






SL-07-BRS

SL-07-SS

ORDERING INFORMATION CATALOG NO. DESCRIPTION LAMP SHIP WEIGHT SL-07-BLT Cast Aluminum Surface Light 18w S8 #1141 1.0 lbs. SL-07-BRS Cast Brass Surface Light 18w S8 #1141 1.0 lbs. SL-07-SS 316 Stainless Steel Surface Light 18w S8 #1141 1.0 lbs. SL-07-MR8-BLT Cast Aluminum Surface Light 20w MR8 FL 1.0 lbs. SL-07-MR8-BRS Cast Brass Surface Light 20w MR8 FL 1.0 lbs. SL-07-MR8-SS 316 Stainless Steel Surface Light 20w MR8 FL 1.0 lbs.

FOLLOWING -SP MODELS COME SUPPLIED WITH BLACK PVC TELESCOPIC POST FOR GROUND MOUNTING

SL-07-SP-BLT	Cast Aluminum Surface Light, PVC Post	18w S8 #1141	1.0 lbs.
SL-07-SP-BRS	Cast Brass Surface Light, PVC Post	18w S8 #1141	1.0 lbs.
SL-07-SP-SS	316 Stainless Surface Light, PVC Post	18w S8 #1141	1.0 lbs.
SL-07-SP-MR8-BLT	Cast Aluminum Surface Light, PVC Post	20w MR8 FL	1.0 lbs.
SL-07-SP-MR8-BRS	Cast Brass Surface Light, PVC Post	20w MR8 FL	1.0 lbs.
SL-07-SP-MR8-SS	316 Steel Surface Light, PVC Post	20w MR8 FL	1.0 lbs.



LIGHT DISTRIBUTIONS AND PHOTOMETRICS

Feet					1		candle lux)		eters			Fee	et		3	6		9	12		Type:
5									1.5			Mete	rs	-	1	2		3		Beam	Job Na
4															1.5 .15	2.4	3	.7	'	(m)	Cat. No
3						1.			1.0		20					X				(11)	Lamp(
2 1		- 0.3 (3)					3 (25)		0.5		M				1	46					Specifi
		.3 (14)					1 (76)		0		23	FL	7			46°	1 2 °				Contra
0	Heig	ht of fixtu 2 3	ure fr 4	om fle 5	6	7 (510m 8	m) 9	Feet											foot-	Notes:
o	0	.5 1.0)	1.5	2	.0	2.5		Meters						7.6 64	/16.9 96		4 6 11		candles (lux)	FOCIN
	S	L-07 ⊦	Half Sj	oread	Photo	omet	rics														FOCUS 25301 LAKE F
	exture dard)	Antiq Verc	lue le	E	Bron extu	ze Ire		Cam	iel	White Texture		unter exture		Rust	V	Veather Iron	ed	Weat Bro	hered wn	Stucco	Rubbe Verd

-HTX

-WIR

-RST

-WBR

-STU

-WTX





	JOBINE								
	Туре:			Date	e:				
	Job Name:								
)	Cat. No.:								
	Lamp(s):								
	Specifier:								
	Contractor:								
	Notes:								
	25301 COM	OUSTRIES INC MMERCENTRE ST, CA 92630	DRIVE	www.focusindustries.com sales@focusindustries.com (949) 830-1350 • FAX (949) 830-3390					
	Rubbed Verde	Chrome Powder	Terra Cotta	Acid Rust	Acid Verde	Black Acid Treatment			
	-RBV	-CPR	-TRC	-BAR/CAR	-BAV/CAV	-BAT			
				BRAS	S & COPPER ONI	Y			

-BLT SL-07 Cut Sheet 072712

-ATV

-BRT

-CAM