SURFACE STEP LIGHTS SL-07 SERIES

TYPE

SPECIFICATIONS

CONSTRUCTION: Cast aluminum, cast brass or 316 Stainless Steel "Hockey Puck" style **LENS:** Sand blasted tempered flat glass

LAMP SUPPLIED: 18w S8 #1141; 1200 hours average rating (25w max) LAMP SUPPLIED -MR8 MODELS: 20w MR8 FL; 2000 hours average rating (20w max)

LAMP OPTIONS: We recommend 10,000 hours average rating Xenon (-X) or Halogen (-H) or 3w 50,000 hours average rating OMNI-3 LED (-LED3)

SOCKET: Single contact bayonet, brass nickel plated lamp socket screw shell (Ba15s); double contact bayonet base (Ba15d) for 120v; both with 200°C silicone lead wires **SOCKET -MR8 MODELS:** High temp ceramic GU5.3 bi-pin with 250°C silicone lead wires

WIRING: Black 5 foot 18/2 zip cord from base of fixture (12v only) For 25 foot 16/2 fixture lead wire add -25F to catalog number. 120v Standard wiring

CONNECTION: FA-05 Quick Connector (not supplied) from fixture to main cable (12/2, 10/2 or 8/2 only) 12v only

MOUNTING: Back plate and hardware supplied

FINISH: Aluminum - Black texture polyester powder coat. Optional finishes available Brass - Unfinished brass. Optional finishes available Stainless Steel - Brushed





SL-07-SS

ORDERING INFORMATION CATALOG NO. DESCRIPTION LAMP SHIP WEIGHT SL-07-BLT Cast Aluminum Surface Light 18w S8 #1141 1.0 lbs. SL-07-BRS Cast Brass Surface Light 18w S8 #1141 1.0 lbs. SL-07-SS 316 Stainless Steel Surface Light 18w S8 #1141 1.0 lbs. SL-07-MR8-BLT Cast Aluminum Surface Light 20w MR8 FL 1.0 lbs. SL-07-MR8-BRS Cast Brass Surface Light 20w MR8 FL 1.0 lbs. SL-07-MR8-SS 316 Stainless Steel Surface Light 20w MR8 FL 1.0 lbs.

FOLLOWING -SP MODELS COME SUPPLIED WITH BLACK PVC TELESCOPIC POST FOR GROUND MOUNTING

SL-07-SP-BLT	Cast Aluminum Surface Light, PVC Post	18w S8 #1141	1.0 lbs.
SL-07-SP-BRS	Cast Brass Surface Light, PVC Post	18w S8 #1141	1.0 lbs.
SL-07-SP-SS	316 Stainless Surface Light, PVC Post	18w S8 #1141	1.0 lbs.
SL-07-SP-MR8-BLT	Cast Aluminum Surface Light, PVC Post	20w MR8 FL	1.0 lbs.
SL-07-SP-MR8-BRS	Cast Brass Surface Light, PVC Post	20w MR8 FL	1.0 lbs.
SL-07-SP-MR8-SS	316 Steel Surface Light, PVC Post	20w MR8 FL	1.0 lbs.



LIGHT DISTRIBUTIONS AND PHOTOMETRICS

Feet				candles lux)	Meters		Fee	t	3	6	9	12		Туре:	
5			(iux)	1.5		Meter	rs	1	2	3		Beam	Job Name:	
4					1.0				0.5 0.15	2.4 \0.74	3.7	V	(m)	Cat. No.:	
3				0 (11)	1.0		20w MR8			X				Lamp(s):	
1	1.3 (14)			3 (25) 1 (76)	0.5		23°FL			170 46°				Specifier:	
	leight of fixture fr				0				1				60.04	Contractor	:
0 0	1 2 3 4 0.5 1.0	5 (1.5	5 7 2.0	8 9 2.5	Feet Meters				67.6	16.9	7.5		foot- candles	Notes:	
SL-07 Half Spread Photometrics									FOCUS INE 25301 CON LAKE FORE	MM					
Black Text (Standa			onze xture	Ca	amel	White Texture	Hunter Texture	Rus	t V	Veathere Iron	d Weatl Bro		Stucco	Rubbed Verde	
-BLT	-ATV	-	BRT	-0	АМ	-WTX	-HTX	-RS	τ	-WIR	-w	BR	-STU	-RBV	







	JOB INFORMATION								
	Туре:			Date	2:				
	Job Name:								
)	Cat. No.:								
	Lamp(s):								
	Specifier:								
	Notes:								
	FOCUS INDUSTRIES INC. 25301 COMMERCENTRE DRIVE LAKE FOREST, CA 92630		www.focusindustries.com sales@focusindustries.com (949) 830-1350 • FAX (949) 830-3390						
	Rubbed Verde	Chrome Powder		Acid Rust	Acid Verde	Black Acid Treatment			
	-RBV	-CPR		-BAR/CAR	-BAV/CAV	-BAT			
				BRAS	S & COPPER ONI	Y			