


1128QC: 6" New Construction IC Recessed Housing with "Quick Connects"



Dimensions:

Diameter: 6 3/8"
Length: 13 1/2"
Width: 10 3/4"
Height: 7 7/8"

Weight: 2.3 lbs.

Wire: 6 1/2" (color/Black/White)

Features:

- Easily converts to LED with optional replacement lamps
- Meets Title 24 energy efficiency standards
- Listed for use with direct contact to insulation

Material List:

1 Body - Aluminum - Raw Steel

Safety Listing:

Safety Listed for Damp Locations
Safety Listed for Damp Locations



Instruction Sheets:

Bilingual (English - French) (HC-438FB)

Collection: Recessed Lighting

This IC recessed light housing features an air-tight application providing quality illumination while offering energy efficiency and lower operating costs. Also features "Quick Connect" wiring for ease of installation.

This IC recessed light housing features an air-tight application providing quality illumination while offering energy efficiency and lower operating costs.

QC - includes Quick Connect wire connectors for easy installation

Featured in the decorative Recessed Lighting collection

Bulb selection for recessed lighting depends on both the trim and housing selection; refer to the manufacturer's website for correct lamping instructions

Housing Adjustment: Housing adjusts vertically for various ceiling thicknesses.

Airtight Construction: Meets airtight requirements for 2.0 CFM or less air leakage.

Joist Tab: Tab to locate on bottom of joist.

UPC #:785652011283

Finish: Not Applicable ()

Shipping Information:

| Package Type | Product # | Quantity | UPC | Length | Width | Height | Cube | Weight | Fr. Class | UPS Ship |
|--------------|-----------|----------|----------------|--------|-------|--------|--------|--------|-----------|----------|
| Individual | 1128QC | 1 | 785652011283 | 14.75 | 10.75 | 8 | 0.734 | 2.55 | 100 | Yes |
| Master Pack | | 6 | 10785652011280 | 22.25 | 20 | 8.75 | 2.253 | 18.15 | 100 | Yes |
| NJ Pallet | | 192 | | 48 | 40 | 75 | 83.333 | 580.8 | | No |
| NV Pallet | | 192 | | 48 | 40 | 75 | 83.333 | 580.8 | | No |

Trim



1120-15

6" Open Trim

White Steel Trim
Maximum Wattage:
75w PAR30L
65w BR30
13.5w A19
15w PAR30L
15w BR30



1125-14

6" Aluminum Baffle Trim

White Trim / Baffle Aluminum
Baffle
White Trim / Baffle Aluminum Trim
Maximum Wattage:
13.5w A19
15w PAR30L
15w BR30
50w PAR30S
75w PAR30L
65w BR30



1126-14

6" Steel Baffle Trim

White Trim / Baffle
Maximum Wattage:
13.5w A19
15w PAR30L
15w BR30
75w PAR30L
65w BR30
50w PAR30S



1126-15

RECESSED TRIM

Black Steel Baffle
White Steel Trim
Maximum Wattage:
75w PAR30L
65w BR30
50w PAR30S
13.5w A19
15w PAR30L
15w BR30



1133AT-15

6" Flat Glass Shower Trim

White
Satin White Glass Diffuser
Maximum Wattage:
40w A19
8w A19
Suitable For Shower Light



1134-68

6" Drop Acrylic Shower Tr

White Plastic Plastic Diffuser
White Plastic Trim
Maximum Wattage:
40w A19
8w A19
Suitable For Shower Light



1135AT-15

RECESSED TRIM

Smooth White Glass Diffuser
White Steel Trim
Maximum Wattage:
40w A19
8w A19



1136-15

6" Eyeball Trim

White
White Steel Trim
Maximum Wattage:
75w PAR30L
65w BR30
15w PAR30L
15w BR30



1136AT-15

6" Eyeball Trim

White
White Steel Trim
Maximum Wattage:
75w PAR30L
65w BR30
15w PAR30L
15w BR30



1151AT-14

6" Baffle Trim

White Trim / Baffle
Maximum Wattage:
50w PAR30S
75w PAR30L
90w PAR38
65w BR30



1151AT-15

RECESSED TRIM

Black Aluminum Baffle
White Aluminum Trim
Maximum Wattage:
50w PAR30S
75w PAR30L
90w PAR38
65w BR30



1154AT-14

6" Open Cone Shower Trim

White Trim / Baffle Aluminum Baffle
White Trim / Baffle
Maximum Wattage:
90w PAR38
50w PAR30S
75w PAR30L
Suitable For Shower Light



1155AT-15

6" Fresnal Glass Shower T

White
Clear Glass Diffuser
Maximum Wattage:
40w A19
8w A19
Suitable For Shower Light