

5921593S-15:



Delivered Lumens: 3360

Input Voltage: 100 - 277Vac

Three CCT color options built-in, simply select between 3000K, 4000K, and 5000K with the touch of a switch.

Two mounting options are available - surface mount to standard junction boxes and recessed mount / T-grid installation.

UPC #:785652083235

Finish: White (15)

Dimensions:

Length: 47 5/8" Wire: 8 1/2" (color/Black/White)

Width: 11 7/8" Bulb Base: Integrated

Height: 11/16" Volts: 120

Watts: 32

Watts Consumed: 32

Watts Rated: 32

Hours Rated: 50000

Lumens: 3500

Bulb Temp: 3000 °K

CRI: 80

Features:

- This advanced LED technology is carefully designed and selected to consist of the highest quality LED chipsets for superior performance and reliability.
- Meets Title 24 energy efficiency standards
- Integrated LED fixtures that meet the high efficacy LED standards set forth in Title 24 and are listed in the California Energy Commission Appliance database.

Material List:

1 Light Guide - Steel - Undefined

1 Mounting Plate - Galvanized Steel - Undefined

1 Lens - Polycarbonate - Undefined

Safety Listing:

Safety Listed for Damp Locations

Shipping Information:

Package Type	Product #	Quantity	UPC	Length	Width	Height	Cube	Weight	Frt. Class	UPS Ship
Individual	5921593S-15	1	785652083235	49.75	14	3	1.209	13.4	93	Yes
Master Pack	5921593S-15	4	10785652083232	50.25	12.25	14.5	5.165	56.7	93	Yes
NJ Pallet		48		48	40	63.5	70.556	680.4		No
NV Pallet		48		48	40	63.5	70.556	680.4		No