


# Product Specifications Report

<b>Job Name:</b>		<b>Job Type:</b>	
<b>Comments:</b>		<b>Quantity:</b>	
<b>Product Number: 9380-15</b>		<b>Dimensions:</b>	
 <p><b>9380-15 - White Wiring Connector</b>                  White Polycarbonate Wiring Connector</p> <p>Polycarbonate tap off connector. Use to tap off of low voltage Ambiance® cable and create a parallel run for shelving, ect. Corrosion resistant contacts pierce the specially designed Ambiance® cable for electrical connection. UL and C-UL listed 12v and 24v. Wet location 12v only. Maximum wattage after connector on 105°C Ambiance® tap cable: 200 at 12v; 375w at 24v.</p> <p><b>UPC #:</b> 785652938054      <b>Product Type:</b> Ambiance LX  <b>Finish:</b> White (15)</p>		<b>Length:</b> 1 1/2"	<b>Switch Type:</b> N/A
		<b>Width:</b> 1 1/2"	<b>Mounting Proc.:</b> N/A
		<b>Height:</b> 7/16"	
		<b>Material List:</b>	
		1 Body - Polycarbonate - White	
		<b>Safety Listing:</b>	
		cUL Listed for Wet Locations UL Listed for Wet Locations	
		<b>Instruction Sheets</b>	
		English (HC-126)	

Shipping Information									
Package Type	Quantity	UPC	Length	Width	Height	Cube	Weight	UPS Ship	Label
Individual	1	785652938054	0.5	4	2.2	0.003	0.04	Yes	
Master Pack	10	10785652938051	1.5	6	4	0.021	0.4	Yes	
NJ Pallet	35000		48	40	60	66.667	1428	No	
NV Pallet	35000		48	40	60	66.667	1428	No	