

96118S-32: Lx LED Clear Festoon Lamp - 3000K 12v

# **Dimensions:**

**Bulb Appearance:** 

Job Type:

Quantity:

Gas Filled:

Bulb Type: LED

Bulb Base: festoon

**Volts:** 12 **Watts:** 0.6

Watts Consumed: 0.648

Watts Rated: 0.6

Hours Rated: 35000

Bulb Temp: 3000 °K

CRI: 85



It's a snap to upgrade existing xenon linear systems to energy saving, money saving lighting.

No need to replace or re-invest in your entire system.

The LED festoon is an opportunity to retrofit or replace traditional under-the-counter systems and fills the need to provide "green" lighting solutions.

Applications: Task & accent lighting for undercabinet, coves, toe-kick spaces and so much more. Directional nature of LED is ideal for in-cabinet lighting.

Retrofit/Remodel Installations for Magnetic Transformer Systems - JUST REPLACE THE LAMP!

Compatible as a retrofit for existing Lx xenon lamp and compatible xenon lamp systems.

Note: The unique design of the PCB (Printed Circuit Board) makes over voltage due to under capacity a non-issue.

Retrofit/Remodel Installations for Electronic Transformer Systems 60w zero-load LED driver available for replacing electronic transformers due to minimum load requirement. Available drivers: 96223S-12 & 96223S-15.

Product Features: Ease of installation. Ease of retrofit/remodel. Bendable/flexibility of the system.

Dimmability: Dimmable with standard incandescent dimming switch.

A "Fit & Forget" Solution: Offering 35,000 hours of useful life (equivalent to 30 years at 20 hours of use per week)

Efficacy Warm White: 40 Lumens/Watt

Color Rendering: 3000K - CRI 90+

## Features:

 LED's energy savings and long life helps protect the environment by using less energy and keeping numerous other types of lamps, with shorter life, out of land-fills

# **Material List:**

#### Safety Listing:

ETL Listed for Damp Locations cETL Listed for Damp Locations

### **Instruction Sheets:**

Trilingual (English, Spanish, and French) (HC-1715FS)

LED Festoon Product Line Options & Features:
12v and 24v
Warm (3000K)
Cool (4000K)
Clear lens for optimal performance
Frosted lens to reduce glare
Color-coded PCB to visually distinguish between warm and cool color temperature LED festoons
Color-coded end-caps to identify 12v (white) and 24v (black)
3 Year Warranty

UPC #:785652028045

# **Shipping Information:**

Package Type	Product #	Quantity	UPC	Length	Width	Height	Cube	Weight	UPS Ship
Individual	96118S-32	1	785652028045	2	2	0.75	0.002	0.001	Yes
Master Pack	96118S-32	10	10785652028042	9.25	2.38	1.18	0.015	0.2	Yes
NJ Pallet		25000		48	40	67.5	75	635	No
NV Pallet		25000		48	40	67.5	75	635	No