

HEATED AREA

SPECIFICATION SHEET

HEATSTRIP REGULAR PART NAME:

High intensity electric radiant heater **DESCRIPTION:**

THH2400AUL PART No:

2400 Watts (8200BTU) POWER:

240 volts @ 50 - 60Hz **VOLTAGE:**

10 Amps CURRENT:

53.5 x 6.5 x 2" **DIMENSIONS:**

17.5 lbs WEIGHT:

Gangbox CONNECTION:

CSA/UL E321448 APPROVALS:

PROTECTION RATING: IP55 From water ingress from all

directions

MOUNTING OPTIONS: Suitable for ceiling, wall, beam, fixed

umbrella and recess mounting. Also available with drop down poles or

suspension kit.

MOUNTING HEIGHT:


82" (2.1m) MINIMUM

90 to 105" (2.3 to 2.7m) **OPTIMUM**

Use drop down kit or suspension kit if higher

Note: See the Product Manual for more detail

HEATED AREA 65 ft² (6m2) **INDOOR PROTECTED OUTDOOR ENCLOSED** 52 ft²(4.8m2) OUTDOOR EXPOSED 43 ft² (4m2)



END VIEW

40" MINIMUM

53.5"

Heatstrip USA LLC.

4275 Executive Square

616 Corporate Way,

1-877-222-0063 (Toll Free)

#200

Suite 2-5771,

www.heatstripusa.com

La Jolla, CA, 92037 Valley Cottage, NY 10989

info@heatstripusa.com

