

## **PRODUCT DETAILS:**

- Wattage settings includes: 3W (260 Lumens), 5W (350 Lumens), 8W (475 Lumens), 12W (750 Lumens)
- Three lens options offer versatility in beam spread via an easy to remove and insert assemble - includes: 20° Spot, 40° Flood, 60° Flood
- Suitable for use in wet (outdoor direct rain or sprinkler) locations as defined by NEC and CEC. Meets United States UL Underwriters Laboratories & CSA Canadian Standards Association Product Safety Standards
- Photometrics based off engine photometrics.
- Incorporates CREE LEDs with application performance tested by CREE
- Optimal drive-over protection up to 4,500 lbs
- Optional performance lenses available
- LumaCore Series products carry a lifetime limited warranty

## FLAT TOP WELL LIGHT

## 15702MZ-LMA27K

VARIABLE OUTPUT LED 2700K WELL LIGHT Named after the ruggedly beautiful island off the coast of British Columbia; Hardy Island products are impeccably designed to defy the harshest environments. The LumaCORE LED accent lighting system is an expertly engineered core that withstands the elements and provides the the user with full control over wattage and color temperature.

DETAILS	
FINISH:	Matte Bronze
MATERIAL:	Cast Brass and Aluminum
GLASS:	Clear Lens

DIMENSIONS	
WIDTH:	4.5"
HEIGHT:	4"
DEPTH:	4.5
WEIGHT:	3lb

LIGHT SOURCE	
LIGHT SOURCE:	Integrated LED
LED NAME:	27G4SE-12W
VOLTAGE:	12v
COLOR TEMP:	2700
CRI:	80
INCANDESCENT EQUIVALENCY:	1 x 60w, 45w, 35w, 25w
DIMMABLE:	No

MOUNTING	
LEAD WIRE:	1 X 96"

SHIPPING	
CARTON LENGTH:	7
CARTON WIDTH:	7
CARTON HEIGHT:	13.5
CARTON WEIGHT:	4.5



PHONE: (440) 653-5500

Toll Free: 1 (800) 446-5539