


# Justice Design Group

## Installation Instructions

## Ambiance Collection™ wall sconces

### IMPORTANT

- Justice Design recommends that a licensed electrician install this lighting fixture
- Installation must comply with all building, safety, and electrical codes and requirements
- Disconnect power to the junction box prior to installation
- Do not reconnect power until this fixture is properly installed
- This fixture is designed to mount to a standard metal 4-0 octagonal junction box




### Hardware Pack contains:

- A. 1 - Brass Knurled Nut
- B. 1 - Lock Washer
- C. 1 - Metal Washer
- D. 1 - Rubber Washer
- E. 2 - Wire Nuts
- F. 2 - 3/4" long 8/32 Screws
- G. 1 - 1 3/4" Nipple
- H. 1 - Fixture Bar


1

Attach Fixture Bar to junction box using two (2) 8/32 Screws.



2

Thread Nipple into Fixture Bar. Leave enough length to insure Nipple will protrude through back of fixture.




# Ambiance Collection™ wall sconces

Justice Design Group page 2

3

Connect fixture wires to supply wires using wire nuts (not included). Observe polarity: black to power, white to neutral, and bare copper to green ground. Tuck wires and wire nuts into junction box.



4

Place fixture over Nipple and secure using Rubber Washer (to cushion), Metal Washer (to spread force), Lock Washer (to prevent loosening), and Knurled Nut (to secure). Be careful not to overtighten Knurled Nut or you may damage fixture.

Please see the additional enclosed sheet for care instructions

