

AR PERFORMANCE

AIRFL Cubic Ft. Pe on Hig	r Minute Revolutions Per	POWER USAGE Watts on High (Excludes Lights)	AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt	CFM (Low) RPM (Low) Watts (Low)	3662 48 3
954	8 126	34	282		C C

SPECIFICATIONS

Light Source Downlight Included Yes Downlight Option Integrated Watts (High) Downward-facing Bulbs 1 X 23W 34 Watts (Low) 3 Dimmable Yes Optional Light Kit Available Integrated **Photometrics** 90 Color Rendering Index Kelvin Temperature 3000K **Electrical** Amps (High) 0.44 Amps (Low) 0.06 DC-188 Motor Size DC Motor Type Dimensions Downrod 1 1.00 OD X 6.00" 6.25 DIA Base Backplate Weight 26.40 LBS Height 14.50" Width 65.00" **Mounting/Installation** Minimum Distance from Fan to Floor 7 feet Interior/Exterior Exterior Lead Wire Length 78" Location Rating CSA UL Listed Damp 24.20 LBS Mounting Weight **FIXTURE ATTRIBUTES**

Product/Ordering Information

SKU Style	300365PN Contemporary	Finish UPC	Polished Nickel 783927559690				
Housing							
Fan Primary Control System Diffuser Description Max Stem Tilt	6 Speed DC CoolTouch-Full White Polycarbonate 30.00	Wall Control Included Primary Material	Yes STEEL				

KICHLER

Blade Finish & Specs				
Blade Finish 1 Blade Pitch Blades Included	WALNUT 14 Yes	Blade Material Blade Sweep Number of Blades	ABS 65 3	
Warranty				
www.kichler.com/warranty				
ALSO IN THIS FAMILY				
		φ		
	-			

300365MWH

300365SBK

You can see all products in this family by searching ${\it Kichler.com}$

KICHLER.