© 2023 Kichler Lighting LLC. All Rights Reserved.

## **MOTOR FINISH**



**Brushed Stainless Steel** 

# **BLADE FINISHES**

Silver, Satin Black



Dimmable



(LED) LED Light Kit



# **AR PERFORMANCE**

**AIRFLOW** Cubic Ft. Per Minute on High

4573

Delivered Efficacy (Lumens/Watt)

88

**RPM** Revolutions Per Minute on High

145

POWER USAGE Watts on High (Excludes Lights)

59

AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt

91

# **SPECIFICATIONS**

SPECIFICATIONS				
Performance				
CFM (High) Watts (High)	4573 59	RPM (High) Airflow Efficiency CFM/W (High)	145 91	
Motor Specifications				
Amps (High) Motor Type	0.50 AC Induction	Motor Size Primary Material	153MM X 18MM Steel	
Mounting/Installation				
Minimum Distance from Fan to Floor Lead Wire Length Low Ceiling Adaptable Connector Mounting Style	7.0 feet 78" Yes, Dual Mount Included Yes Downrod	Interior/Exterior Location Rating Max Stem Tilt Direct Wire Wire Connectors	INTERIOR Dry 22.00 Yes Wire Nuts	
Dimensions				
Downrod 1 Downrod 1 - Measurement B Base Backplate Blade Sweep Downrod 2 - Measurement A Downrod 2 - Measurement C Width	1.00 x 4.5" 10.50" 6.5" DIA 52 16.50" 11.50" 52.00"	Downrod 1 - Measurement A Downrod 1 - Measurement C Weight Downrod 2 Downrod 2 - Measurement B Height	19.25" 11.50" 23.30 LBS Dual Mount" 7.00" 19.25"	
Light Source	AC Induction  O.50 AC Induction  Direct From Fan to Floor 7.0 feet Apt Aptable  Aptable  Action Fan to Floor 7.0 feet Aptable  Aptable  Action Fan to Floor 7.0 feet Aptable  Aptable  Aptable  Action Fan to Floor 7.0 feet Aptable  Aptable  Aptable  Action Fan to Floor 7.0 feet Aptable  Aptable  Aptable  Action Fan to Floor 7.0 feet Aptable  Aptable  Action Fan to Floor 7.0 feet Aptable  Action Fan to Floor Aptabl			
Downlight Included Color Rendering Index Lumens/watt (efficacy) Lamp Type # of Bulbs/LED Modules	90 88.00 A19	Initial Lumens Lamp Included Light Source	2400 Included LED	
Photometrics				

Input Voltage 120.00V Supply Wire (Degrees) 90  FIXTURE ATTRIBUTES	Electrical				
FIXTURE ATTRIBUTES	Input Voltage	120.00V	Supply Wire (Degrees)	90	
	FIXTURE ATTRIBUTES				

Blade Finish & Specs

Blade Finish 2 Satin Black Blade Finish 1 Silver Blade Material Wood Hybrid Blade Pitch 12 Blades Included Yes Blades Reversible Yes

Number of Blades 5

**Included Control** 

Wall Control Included No Remote Included No

**Product/Ordering Information** 

SKU Finish **Brushed Stainless Steel** 330162BSS UPC Style 783927006668 Contemporary

Housing

Fan Primary Control System Pull Chain

Warranty

www.kichler.com/warranty

## **Compatible Accessories**

CoolTouch™ Handheld Control System Limited Function White, Universal Fan Remote Control White, Wall Control System Limited Function Multiple Finishes, 60 Degree Slope Adapter Brushed Stainless Steel, Dual Threaded 12" Downrod Brushed Stainless Steel, Dual Threaded 18" Downrod Brushed Stainless Steel, Dual Threaded 24" Downrod Brushed Stainless Steel, Dual Threaded 36" Downrod Brushed Stainless Steel, Dual Threaded 48" Downrod Brushed Stainless Steel, Dual Threaded 60" Downrod Brushed Stainless Steel, Dual Threaded 72" Downrod Brushed Stainless Steel

## **ALSO IN THIS FAMILY**





330162MWH 330162OBB 330162SBK

You can see all products in this family by searching Kichler.com