



Designed to replace a standard light or fan single-pole switch, this occupancy/vacancy sensor is ideal for storage and utility rooms. Includes interchangeable face colors in ivory, light almond and white.

Features & Benefits

Lighted switch for visibility in darkened rooms.

Automatic-ON, Manual-ON, and Selectable Auto/Manual ON.

Adjustable time delay of 30 seconds to 30 minutes.

No neutral required.

Low-profile styling with uniform color-matched lens and device.

Coverage: 180 degrees, max. 600 ft.2 (56m2)

Works with most common residential lighting types.

Load: Incandescent, LED, fluorescent, compact fluorescent (CFL), magnetic low-voltage (MLV) and electronic low-voltage (ELV), 1/6 hp.

For covering patents, see www.legrand.us/patents.

Specifications

General Info

Product Line	Pass & Seymour	UPC Number	785007026351
--------------	----------------	------------	--------------

Country Of Origin	China	Application Sector	Residential
-------------------	-------	--------------------	-------------

Standard	cULus
----------	-------

Technical Information

Target Size	180°	Response Frequency	60 Hz
-------------	------	--------------------	-------

Sensor Type	Occupancy, Vacancy	Wattage	600 W
-------------	--------------------	---------	-------

Sensing Range

600 sq ft

Voltage

120 V, 120 V

Sensitivity

60Hz

Load

120VAC

Environmental Conditions

Indoor Use Only
