


Lighting Your Life Since 1970

Product Specifications - 14404NAWT			
Job Name:	Job Type:		
	,		
Quantity:	Comments		
Quantity.	Comments		
·			



14404NAWT

Bali 1-Light Chandelier



Finish Glass/Shade

*max overall height **Product Category**Single Pendant

Lamping	
Number of Bulbs	1
Light Type	Incandescent
Bulb Type	MB
Max Bulb Wattage	60
Max Fixture Wattage	60
Rated Life	
Rated Lumens	±0
Color Temp	
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	N/A

Measurements	
Width	15.00"
Height	13.00"
Length	15.00"
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	0.00"
Max Overall Height	134.00"
Hanging Weight	2.98 lbs
Height Adjustable	N/A
Slope	120°
Chain Length	N/A
Wire Length	120"
Canopy Width	5.00"
Canopy Height	1.25"
Canopy Length	5.00"

Shipping	
Carton Weight	6.50 lbs
Carton Width	22"
Carton Height	13"
Carton Length	22"
Carton Cubic Feet	3.55
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification Other Equivalents
Safety Pating Dry LIPC Code 783200126589 Incandescer

Safety Rating	Dry	UPC Code	783209126589
Energy Star	No	Shades Included	N/A
CA Title 24	No	Crystals Included	N/A
CA Title 20	No	Diffuser Included	N/A
ADA	No	Conversion Kit	N/A
Dark Sky	N/A	Material	Twine

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2016 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.