


Product	Speci	fications -	24557SSSN
Troduct	SUCCI	ncanons -	・ムオンシノいいいい

	Job Type:
Quantity:	Comments



24557SSSN

**Lucid 6-Light Pendant** 



**Finish** Glass/Shade Satin Nickel

**Product Category** 

Single Pendant

Lamping

Lamping	
Number of Bulbs	6
Light Type	Incandescent
Bulb Type	MB
Max Bulb Wattage	60
Max Fixture Wattage	360
Rated Life	
Rated Lumens	±0
Color Temp	
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	N/A

Measurements
--------------

weasurements	
Width	19.00"
Height	40.00"
Length	19.00"
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	0.00"
Max Overall Height	40.00"
Hanging Weight	14.33 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	180"
Canopy Width	4.75"
Canopy Height	1.00"
Canopy Length	4.75"

## Shipping

Snipping	
Carton Weight	15.96 lbs
Carton Width	21'
Carton Height	33'
Carton Length	21'
Carton Cubic Feet	8.29
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

N/A N/A

Certification Other **Equivalents** 

Safety Rating	Dry	UPC Code	783209131774	Incandescent Watts
Energy Star	No	Shades Included	N/A	Fluorescent Watts
CA Title 24	No	Crystals Included	N/A	
CA Title 20	No	Diffuser Included	N/A	
ADA	No	Conversion Kit	N/A	
Dark Sky	N/A	Material	Metal+Glass+Fabric	

Maxim Lighting International and all designs, logos and images © 2016 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.