


Lighting Your Life Since 1970

Product Specifications - 39104BCPN Job Type: Job Name: Quantity: Comments



39104BCPN

Equinox LED Pendant



Finish Polished Nickel

Glass/Shade Beveled Crystal Measurements *max overall height

Product Category

Single Pendant

Lamping

Lamping		weasurements
Number of Bulbs	15	Width
Light Type	LED	Height
Bulb Type	G9	Length
Max Bulb Wattage	2.3	Extension
Max Fixture Wattage	34.5	Back Plate Width
Rated Life		Back Plate Height
Rated Lumens	±2,850	HCO
Color Temp	±3,500 K	Min Overall Height
Bulb(s)	Included	Max Overall Height
Light Up/Down	N/A	Hanging Weight
Beam Spread	N/A	Height Adjustable
CRI	90+	Slope
Photo Cell Included	N/A	Chain Length
Ballast/Driver/Transformer	No	Wire Length
Dimmable	Yes	Canopy Width
		Canopy Height
		Canopy Length

Shipping

25.00" 29.75" 25.00" N/A N/A N/A N/A 31.50" 110.25" 22.00 lbs Yes N/A 48" 120" 5.80" 1.40" 5.80"

Snipping	
Carton Weight	27.70 lbs
Carton Width	26
Carton Height	32
Carton Length	29
Carton Cubic Feet	13.87
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Oversize

Certification		Other	
Safety Rating	Dry	UPC Code	783209127166
Energy Star	No	Shades Included	N/A
CA Title 24	No	Crystals Included	N/A
CA Title 20	No	Diffuser Included	N/A
ADA	No	Conversion Kit	N/A
Dark Sky	N/A	Material	Steel+Crystal

Equivalents

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2016 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.