


Lighting Your Life Since 1970

Product Specifications - 39108BCTXBPN Job Name: Job Type: Quantity: Comments



39108BCTXBPN Equinox LED Pendant



Finish Textured Black / Polished Nickel

Glass/Shade Beveled Crystal *max overall height

Product Category Single Pendant

Lamping	1
Number	o
Light Tv	n

Number of Bulbs	16+12
Light Type	LED
Bulb Type	G9
Max Bulb Wattage	2.3
Max Fixture Wattage	64.4
Rated Life	
Rated Lumens	±5,320
Color Temp	±3,500 K
Bulb(s)	Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	90+
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard

Measurements

ivieasui ettiettis	
Width	39.75"
Height	46.50"
Length	39.75"
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
НСО	N/A
Min Overall Height	47.25"
Max Overall Height	126.00"
Hanging Weight	59.40 lbs
Height Adjustable	Yes
Slope	N/A
Chain Length	N/A
Wire Length	120"
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

Shipping

Carton Weight	81.30 lbs
Carton Width	41"
Carton Height	50"
Carton Length	41"
Carton Cubic Feet	48.12
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	

Cortification

Other	
UPC Code	783209127203
Shades Included	N/A
Crystals Included	N/A
Diffuser Included	N/A
Conversion Kit	N/A
Material	Steel+Crystal
	UPC Code Shades Included Crystals Included Diffuser Included Conversion Kit

Othor

	/ai	

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2016 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.