

PRODUCT DESCRIPTION

With solid Die-Cast Aluminum construction and powered by a range voltage input driver, Pathfinder is a high performance down light for commercial and residential installations. Choose from triangular or spherical profiles as they discreetly extend from the wall. Available with a photocell option, these archetypal forms purposely blend into the architectural landscape creating safer spaces that shine light on locations of interest. Available in Black, Architectural Bronze, or Metallic Sliver

MEASUREMENTS

DIMENSION : 7" W x 4.5" H x 3.5" Ext

: 2.25" HCO **BACK PLATE** HANGING WEIGHT : 1.51 lb

LAMPING

INPUT VOLTAGE : 120-277V

LUMENS : 880 Rated (820 Del.)

BULB : 1 x 15W LED PCB Integrated, 15W Total

BULB INCLUDED : (Integrated)

DIMMABLE : Only at 120V with ELV

CRI : 80 CRI COLOR_TEMP : 3000K LIGHTING_DIRECTION: Down

FINISHES OPTION

Bronze

Silver

MATERIAL

Aluminum +Acrylic

RATINGS

cETLus Wet Location For OutdoorADA









ADDITIONAL

INSTALL UP/DOWN: Down **PHOTOCELL** RATED LIFE 50000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER)

253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER

4200 SHIRLEY DR. I ATLANTA, GA 30336

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com