CHIP | FLUSH MOUNT

57690 | 57692 | 57694 | 57695 | 57697 | 57699


- Size options: 5," 6.5," 7," and 9"
- Available in 3000k (Made-to-order Color Temperatures available)
- Suitable for Closets according to NEC Section 410.8 & 410.16
- Available in Black (BK), Satin Nickel (SN) and White (WT)
- Dimmable with Triac and ELV Dimmers
- Easy to install: fits in 3-0 and 4-0 Outlet Box (pancake and mud ring acceptable)

 Pendant light accessory available (sold separately)
- Edge-Lit LED Technology
- Suitable for Wet Location, for use on ceilings outdoor and above showers
- cFTLus






Round




Square

PRODUCT DESCRIPTION

This low profile flush mount is our entry level Wafer. Manufactured of a plastic shell with aluminum backing, the Chip brings all the look of the Wafer at economical pricing for residential applications. The bright and even lighting effect is delivered by edge-lit technology offering an upscale surface mount solution to substitute recessed can lighting.





MEASUREMENTS

	IVIL7 (WIRE		
MODEL		L	DIMENSION	LENGHT
	57690	RD	5.25"W x 0.5"H x 5.25"L	8"L
	57692	RD	7"W x 1.25"H x 7"L	8"L
	57694	RD	9" W x 1.25" H x 9"L	6"L
	57695	SQ	5"W x 0.5"H x 5"L	8"L
	57697	SQ	6.4"W x 0.5"H x 6.4"L	8"L
	57699	SQ	8.5" W x 0.75" H x 8.5"L	8"L

LAMPING

LAWIF	ING		COL	LUMENS		
MODEL	BULB TYPE	CRI	TEMP.	DEL	DIMMABLE	INPUT
57690	12W PCB Integrated LED	90+	3000K	900	Triac CL/ELV	120V
57692	16W PCB Integrated LED	90+	3000K	1050	Triac/ELV	120V
57694	18W PCB Integrated LED	90+	3000K	1200	Triac/ELV	120V
57695	12W PCB Integrated LED	90+	3000K	930	Triac CL/ELV	120V
57697	15W PCB Integrated LED	90+	3000K	1050	Triac CL/ELV	120V
57699	18W PCB Integrated LED	90+	3000K	1260	Triac CL/ELV	120V

Always consult a qualified electrician before installing any lighting product

FINISHES OPTIONS:

Satin Nickel (SN)

White (WT)

Black (BK)



Polycarbonate + Steel

GLASS:

White

AVAILABLE SIZE:

5" | 6.5" | 7" | 9"

RATINGS:

CETLUS Wet Location Title 24 JA8 Compliant **Energy Star** ADA













INSTALL UP/DOWN: UP RATED LIFE: 50,000 hours **OPERATING TEMPERATURE:** -20°C (-4°F), 40°C (104°F)



101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com