
CHIP | FLUSH MOUNT


57690 | 57692 | 57694 | 57695 | 57697 | 57699

- Size options: 5," 6.5," 7," and 9"
- Available in 3000k (Made-to-order Color Temperatures available)
- Suitable for Closets according to NEC Section 410.8 & 410.16
- Available in Black (BK), Satin Nickel (SN) and White (WT)
- Dimmable with Triac and ELV Dimmers
- Easy to install: fits in 3-0 and 4-0 Outlet Box
- (pancake and mud ring acceptable) • Pendant light accessory available (sold separately)
- Edge-Lit LED Technology
- Suitable for Wet Location, for use on ceilings outdoor and above showers
- cETLus





Round



Square

PRODUCT DESCRIPTION


This low profile flush mount is our entry level Wafer. Manufactured of a plastic shell with aluminum backing, the Chip brings all the look of the Wafer at economical pricing for residential applications. The bright and even lighting effect is delivered by edge-lit technology offering an upscale surface mount solution to substitute recessed can lighting.

13.1.27

L

н⊏

W



MEASUREMENTS

		WIRE		
MODEL			DIMENSION	LENGHT
	57690	RD	5.25"W x 0.5"H x 5.25"L	8"L
	57692	RD	7"W x 1.25"H x 7"L	8"L
	57694	RD	9" W x 1.25" H x 9"L	6''L
	57695	SQ	5"W x 0.5"H x 5"L	8''L
	57697	SQ	6.4"W x 0.5"H x 6.4"L	8''L
	57699	SQ	8.5" W x 0.75" H x 8.5"L	8''L

LAMPING

			COL	LUMENS			
MODEL	BULB TYPE	CRI	TEMP.	DEL	DIMMABLE	INPUT	
57690	12W PCB Integrated LED	90+	3000K	750	Triac CL/ELV	120V	
57692	16W PCB Integrated LED	90+	3000K	1100	Triac/ELV	120V	
57694	18W PCB Integrated LED	90+	3000K	1250	Triac/ELV	120V	
57695	12W PCB Integrated LED	90+	3000K	900	Triac CL/ELV	120V	
57697	15W PCB Integrated LED	90+	3000K	1050	Triac CL/ELV	120V	
57699	18W PCB Integrated LED	90+	3000K	1250	Triac CL/ELV	120V	

Always consult a qualified electrician before installing any lighting product



WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER 101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com

FINISHES OPTIONS:

Satin Nickel (SN)
White (WT)
Black (BK)
MATERIAL: Polycarbonate + Steel
GLASS: White
AVAILABLE SIZE: 5" 6.5" 7" 9"
RATINGS: cETLus Wet Location Title 24 JA8 Compliant Energy Star ADA
I I I I I I I I I I I I I I I I I I I

INSTALL UP/DOWN: UP RATED LIFE: 50,000 hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)