SKY I FLUSH MOUNT 57762 / 57772 / 57764 / 57774


- Dimmability Options: 0-10V or ELV
- Finish Options: White, Bronze, Brushed Aluminium
- Suitable for Closets according to NEC Section 410.8 & 410.16
- LED 3000K/4000K Color Temperature, CRI 90+
- Suitable for Wet Location
- Energy Star
- ETL/cETL
- 120-277V Input





PRODUCT DESCRIPTION

Sky makes large scale edge lit LED flush mount easy for both residential and commercial uses. With a user-friendly mounting bracket and integrated driver, this product lends itself to quick installations. High powered LED modules with 110-277V capability with your choice of dimming and classic finishes to suit any setting.



MEASUREMENTS

LA	M	PI	Ν	G
----	---	----	---	---

	DIMENSION			CD I	LUMENS			INIDUT
MODEL	DIMENSION	MODEL	BULB TYPE	CRI	RATED DEL	IEMP.	DIMMABLE	INPUT
57762	11.75"L x 0.75"W x 23.5"L	57762	22W PCB LED (Integrated)	90+	2000 1760	3000K	ELV	120V -277
57772	11.75"L x 0.75"W x 23.5"L	57772	22W PCB LED (Integrated)	90+	2000 1760	4000K	ELV	120V -277
57764	11.75"L x 0.75"W x 48"L	57764	45W PCB LED (Integrated)	90+	4000 3800	3000K	ELV	120V -277
57774	11.75"L x 0.75"W x 48"L	57774	45W PCB LED (Integrated)	90+	4000 3800	4000K	ELV	120V -277

FINISHES OPTIONS:

White	(WT)
Bronze	e (BZ)

Brushed Aluminium (AL)



*57772 is only stocked in WT (White finish). Other finishes accepted by request, MOQ may apply.

MATERIAL:

Aluminum + Acrylic

RATINGS:

ETL/cETL IP65 Wet Location Energy Star Title 24 Closets Rated: NEC 410.8 & 410.16



ADDITIONAL: RATED LIFE: 50,000 Hours OPERATING TEMP: -20° C (-4°), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product



WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER 4200 SHIRLEY DR. I ATLANTA, GA 30336

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com