


Product	Specification	s - 60136W	APC
Troduct	Directification	15 - 001.20 ** /	71 C

Job Name:	Job Type:
Quantity:	Comments



60136WAPC

Hotel LED 1-Light Pendant



*max overall height

Product Category

Single Pendant

Finish Polished Chrome

Lamping	
Number of Bulbs	1
Light Type	LED
Bulb Type	MB
Max Bulb Wattage	16
Max Fixture Wattage	16
Rated Life	
Rated Lumens	±1,120
Color Temp	3000k
Bulb(s)	Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	90+
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	CL/ELV Dimmer

Glass/Shade

Measurements	
Width	14.25"
Height	35.50"
Length	36.00"
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	35.50"
Max Overall Height	72.50"
Hanging Weight	7.28 lbs
Height Adjustable	Yes
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

Shinning

Snipping	
Carton Weight	11.46 lbs
Carton Width	9"
Carton Height	6"
Carton Length	38"
Carton Cubic Feet	1.19
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification

Other

_	-			-
-	,,,,,	12	Δr	7 t c
_4	un	ra i	C1	ILC

Safety Rating	Dry	UPC Code	783209129115	Incandescent Watts	N/A
Energy Star	No	Shades Included	N/A	Fluorescent Watts	N/A
CA Title 24	No	Crystals Included	N/A		
CA Title 20	No	Diffuser Included	N/A		
ADA	No	Conversion Kit	N/A		
Dark Sky	N/A	Material	Steel+Fabric Shade		

Maxim Lighting International and all designs, logos and images © 2016 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.