



ACCESSORIES (Sold Separately)




FCT6000WT Wall Control

PRODUCT DESCRIPTION

Boldly beveled tapered glass panels are arranged around a metal frame finished in either Chestnut Bronze or elegant Golden Silver. Evocative of an earlier era, the glitz and glamor of the Odeon collection integrates Wifi-enabled functions to dim the LED bulbs provided and operate the fan controls. Transform your fan with a dazzling Smart Fan-delight.

- Always consult a qualified electrician before installing any lighting product
- Installation Requirements:

Ceiling fan attaches to electrical junction box securely anchored and capable of withstanding at least 35 lbs



MEASUREMENTS
DIMENSION
MAX OAH
CANOPY
HANGING WEIGHT

LAMPING

INPUT VOLTAGE LUMENS BULB DIMMABLE CRI

: 32.75" D x 22.75" H : 22.75" OAH : 6.75" W x 2.75" H x 6.75" L

:120V

: 36.93 lb

: 2,650 Rated (2,380 Del.) : 8 x 4W E12 LED , 32W Total : By Control Provided

: 80 CRI COLOR_TEMP : 3000K

ENERGY INFORMATION AT HIGH SPEED

AIRFLOW	: 2440 CFM
ELECTRICITY USE	: 20W
AIRFLOW EFFICIENCY	: 122 CFM / W



MATERIAL Glass+Steel+ABS

RATINGS

cFTLus **Damp Location**

INCLUDES

- Wall Mountable Remote Control
- 1 x 8" Downrod

DOWNROD OPTIONS

- 18" (FRD0118BK, GS)
- 24" (FRD0124BK, GS)
 30" (FRD0130BK, GS)
- 36" (FRD0136BK, GS)



ADDITIONAL

OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)



WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER 4200 SHIRLEY DR. I ATLANTA, GA 30336

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com