## INSTALLATION INSTRUCTIONS

Item#N6550-690 (New. 2021/05/10)

### **READ AND SAVE THESE INSTRUCTIONS**

# WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER. AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

### **MOUNTING THE FIXTURE (Fig.1)**

- Shut off power at the fuse box or circuit breaker box and remove the old fixture including the mounting hardware.
- 2. Carefully unpack your new fixture and lay out all the parts in a clear area. Take care not to misplace any small parts necessary for installation.
- 3. Loosen screws (D) to remove mounting plate (A) from fixture body (C).
- Attach mounting plate (A) using mounting screws (B) (Size: #8-32N\*L0.5") to the junction box (not included). The side of the mounting plate marked "GND" must face out.
- 5. Place plastic washer (F) over all thread (G). Screw fixture loop (E) to all thread (G).

### **CONNECTING THE WIRES (Fig. 2)**

6. Connect the electrical wires as shown in Fig. 2, making sure that all wire connectors are secured. If your junction box has a ground wire (green or bare copper), connect the fixture's ground wire to it. Otherwise, connect the fixture's ground wire directly to the mounting plate (A) using the green screw provided.

Tuck wire connections neatly into junction box.

#### FINISHING THE INSTALLATION (Fig.1)

- 7. Place fixture body (C) over mounting plate (A), and secure with screws (D).
- 8. Place candle covers (K) over sockets (J).
- Install (2) two candelabra base bulbs (L) up to 60 watts each or CFL or LED equivalent (not included) in accordance with the fixture specification. —DO NOT EXCEED THE MAXIMUM WATTAGE RATING! (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)
- 10. Attach crystal drop (I) on finial (H).

Your installation is now complete. Return power and test the fixture.

Note: Illustration (Fig.1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.





