

INSTALLATION INSTRUCTIONS

Item#N6964-1 (Rev. 11/25/2015)

READ AND SAVE THESE INSTRUCTIONS

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.
AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

HANGING THE FIXTURE (Fig. 1)

1. Carefully remove the fixture from the carton and check that all parts are included as shown in the illustration.
2. Shut off power at the circuit breaker and remove old fixture including the mounting hardware.
3. Place the Canopy (L) to the Nipple (M) on the top of Fixture body.
4. Find the predrilled holes in the Circular Strap (A) that have indentations on each side. Thread the two Screw Studs (B) from the indented side into the Circular Strap (A) then out from the raised side of the Circular Strap (A). Thread Nuts (D) on the Screw Studs (B) until tightly secured.
5. Attach the Circular Strap (A) to the Outlet Box using the two screws (C). The side of the Circular strap marked "GND" should face out.
6. Loosen the Screws (E), make the Fixture Body (F) to separate Metal Frame (K).
7. Insert the Large Glass Panels (H) into the Fixture Body (F), secure with clips on the bottom.
8. Pry up the Clips on the bottom of Metal Frame (K), place the Glass Shield (J) into bottom Metal Frame (K), then insert the small Glass Panels (I) into Metal Frame and secure with clips on the bottom.
9. Align the holes on the bottom Metal Frame (K) to Fixture Body (F) and secure with Screws (E).
10. Install the light bulbs (not included) in accordance with the fixture's specifications. **(DO NOT EXCEED THE MAXIMUM WATTAGE RATING!) (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)**

CONNECTING THE WIRES (Fig. 2)

11. At this point, connect the electrical wire as shown in (Fig.2), making sure that all wire connectors are secured. If your outlet has a ground wire (green or bare copper), connect the fixtures Ground Wire to it. Otherwise, connect the fixture Ground Wire directly to the circular strap using the Green Screw provided.

FINISH THE INSTALLATION (Fig. 1)

12. After the wires are connected, carefully tuck them inside the outlet box. Then place the Canopy (L) over Screw Studs (B) and secure against ceiling with Knurled Knobs (G).

Your installation is now complete. Return power to the junction box and test the fixture.

Note: Illustration (Fig.1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.

