

NL-680

6" Fully Adjustable Elbow

Type

Project

Catalog No.

Notes

FEATURES

Trim: Metal trim with fully adjustable elbow can be adjusted up 358° horizontally and 70° vertically. Adjustable elbow allows lamp to be front loaded into trim.

Mounting: Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86).

COMPATIBLE LAMP / HOUSINGS

Low Voltage:

50W 12V MR16 max. (NLIC-601 Series; NL-601 Series; NLR-604 Series)

75W 12V MR16 max. (NL-601/75 Series; NLR-604/75 Series)

Retrofit Kits:

50W 12V MR16 max. (NLK-2600)

See individual housing specification sheets for more information.

LABELS AND LISTINGS

cULus Listed for Damp Location when used with compatible housing




PRODUCT IMAGES & DIMENSIONS



NL-680BZ



NL-680W



6" Fully Adjustable Elbow

Catalog No.

NL-680BZ = 6" Bronze Fully Adjustable Elbow

NL-680W = 6" White Fully Adjustable Elbow

Compatible Housings

Catalog No.

Low Voltage

NL-601Q = Non-IC New Construction / 120V Magnetic / 50W max.

NL-601/1EL = Non-IC New Construction / 120V Electronic / 50W max.

NL-601/2EL = Non-IC New Construction / 277V Electronic / 50W max.

NL-601/75/1EL = Non-IC New Construction / 120V Electronic / 75W max.

NL-601/75/2EL = Non-IC New Construction / 277V Electronic / 75W max.

NLIC-601QAT = ICAT New Construction / 120V Magnetic / 50W max.

NLR-604/1EL = Non-IC Remodel / 120V Electronic / 50W max.

NLR-604/2EL = Non-IC Remodel / 277V Electronic / 50W max.

NLR-604/750 = Non-IC Remodel / 120V Magnetic / 75W max.

NLR-604/75/1EL = Non-IC Remodel / 120V Electronic / 75W max.

NLR-604/75/2EL = Non-IC Remodel / 277V Electronic / 75W max.

Low Voltage Retrofit Kits

NLK-2600 = Non-IC / 120V Magnetic

Example: NL-680B = 6" Black Fully Adjustable Elbow