NMT-303/24C2D1 / NMT-303/24C2D2

24V Class II Dimmable Hardwire Magnetic LED Driver with Breakers

Source: 120V or 277V Input / 24V Output 300W (3 x 100W Breakers)

Type **Project** Catalog No. Notes

PRODUCT DESCRIPTION

24V enclosed dimmable driver to be used with Nora Lighting's 24 Volt systems requiring a Class II driver. Three breakers each produce 100 watts and can be dimmed with low voltage magnetic dimmer. Includes a regulator to provide constant current and constant voltage.

FEATURES

- · Low voltage magnetic dimming
- Integral regulator for constant current and voltage
- · Manual Reset Overload Protection for each Class II Circuit
- Indoor/Outdoor Enclosure Type 3R Enclosure
- Conduit Access Wiring Compartment
- Made in USA
- · Meets Class II output limits
- 24 Volt DC Rated output
- · UL Recognized
- Available in 120V or 277V

ELECTRICAL

Input Voltage: 120V or 277V (must specify) Output Voltage: 24VDC, 4A per circuit max.

Wattage: 3 x 100W

Dimming: Magnetic Low Voltage

Regulator: Constant Current and Constant Voltage

COMPATIBLE NORA 24V SYSTEMS

LED Drivers are compatible with Nora Lighting's 24V systems

SERIES	DESCRIPTION
NMP2-A	24V Josh Adjustable
NMP2-LED	24V Josh Fixed
NUTP1	24V Standard Tape Light (Silicone Encapsulated
NUTP3	24V RGB Color Changing Tape Light
NUTP5	24V Hy-Brite Tape Light
NUTP7	24V Standard Tape Light (Non-Encapsulated)
NUTP8	24V High Output Tape Light
NUTP9	24V Side-Lit Tape Light
NUTP10	24V CCT Color Changing Tape Light
NUTP11	24V RGBW Color Changing Tape Light
NUTP12	24V Comfort Dim Tape Light
NUTP51	24V Continuous Hy-Brite Tape Light
<u>NUTP71</u>	24V Continuous Standard Tape Light
NUTP81	24V Continuous High Output Tape Light

24V Lightbar Silk SBC

OPTIONAL ACCESSORIES

NULB

NALTL-10: 10' Power Line Connector NALTL-30: 30' Power Line Connector


NATL-302W: Power Line Splitter, white cable. Splits power line connector into two separate connections.

LABELS AND LISTINGS

- 3-Year Limited Warranty
- cULus Recognized Driver



PRODUCT IMAGES & DIMENSIONS



NMT-303/24C2D1 / NMT-303/24C2D2

24V Class II Dimmable Hardwire Magnetic LED Driver



NALTL-10 / NALTL-30

Power Line Connector



NATL-302W Power Line Splitter

24V Class II Dimmable Hardwire Magnetic LED Driver with Breakers

Input Voltage / Output Voltage

NMT-303/24C2D1 = 120V input / 24V output NMT-303/24C2D2 = 277V input / 24V output **Optional Accessories** Description

> NALTL-10 = 10' Power Line Connector NALTL-30 = 30' Power Line Connector NATL-302W = Power Line Splitter, White

Example: NMT-303/24C2D2 = 277V/24V 300W Class II Dimmable Hardwire Magnetic LED Driver with (3) 100W Breakers

