

NS-12

4" Surface Gimbal Ring

Type _____

Project _____

Catalog No. _____

Notes _____

FEATURES

Trim: Metal trim with gimbal that can be adjusted up to 20°. Adjustable gimbal allows lamp to be mounted flush with trim.

Mounting: Trim includes three trim clips that securely mount trim in housing. Remove socket from plate and mount lamp into gimbal ring.

COMPATIBLE LAMP / HOUSINGS

Line Voltage:

35W R20/PAR20 max. (NFBIC-4INCATA)

50W R20/PAR20 max. (NS-401QAT; NSIC-401QAT; NSR-404QAT; NSRIC-404QAT)

See individual housing specification sheets for more information.

LABELS AND LISTINGS

* cULus Listed for Damp Location when used with compatible housing



PRODUCT IMAGES & DIMENSIONS




NS-12BZ



NS-12N



NS-12W



4" Surface Gimbal Ring

Catalog No.

NS-12BZ = 4" Bronze Surface Gimbal Ring

NS-12N = 4" Natural Metal Surface Gimbal Ring

NS-12W = 4" White Surface Gimbal Ring

Compatible Housings

Catalog No.

NFBIC-4INCATA = 2-Hour Fire Rated New Construction / 35W max.

NS-401QAT = Non-IC Air-Tight New Construction / 50W max.

NSIC-401QAT = IC Air-Tight New Construction / 50W max.

NSR-404QAT = Non-IC Air-Tight Remodel / 50W max.

NSRIC-404QAT = IC Air-Tight Remodel / 50W max.

Example: **NS-12W** = 4" White Surface Gimbal Ring