## Туре

Project

Catalog No.

Notes

10162

## **PRODUCT IMAGES & DIMENSIONS**

**Compatible Housings** 


NS-4010AT = Non-IC Air-Tight New Construction / 50W max

NSIC-4010AT = IC Air-Tight New Construction / 50W max NS-4010AT/IC = IC Air-Tight New Construction / 15W max NSR-4040AT = Non-IC Air-Tight Remodel / 50W max NSRIC-4040AT = IC Air-Tight Remodel / 50W max

Catalog No.







Mounting: Trim includes three trim clips that securely mount trim in housing.
COMPATIBLE LAMP / HOUSINGS
Line Voltage:
15W R20/PAR20 max. (NS-401AT/IC)
50W R20/PAR20 max. (NS-4010AT; NSIC-4010AT; NSR-4040AT; NSRIC-4040AT)
See individual housing specification sheets for more information.

Trim: High grade albalite lens attached to metal trim.

LABELS AND LISTINGS

• cULus Listed for Wet Location when used with compatible housing



FEATURES

Example: NS-22B = 4" Albalite Lens with Black Metal Trim

4" Albalite Lens with Metal Trim

NS-22B = 4" Albalite Lens with Black Metal Trim

NS-22W = 4" Albalite Lens with White Metal Trim



Catalog No.