

# NT-5070

## 5" BR/PAR30 Eyeball with Metal Trim

Type \_\_\_\_\_

Project \_\_\_\_\_

Catalog No. \_\_\_\_\_

Notes \_\_\_\_\_

### FEATURES

**Trim:** Adjustable metal trim can be rotated 358° horizontally and 30° vertically. Eyeball includes two socket positions for optimum light control and output.

**Mounting:** Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86). Remove socket from socket plate within housing (if applicable), and mount directly onto trim.

### COMPATIBLE HOUSINGS

Compatible with Line Voltage housings. See individual specification sheets for more information.

### LAMP

50W PAR30 Maximum (NHIC-527QAT; NHRIC-527QAT)


75W BR30/PAR30 Maximum (NHIC-501QAT; NHRIC-504QAT; NFBIC-5INCATA)

### LABELS AND LISTINGS

cULus Listed for Damp Locations when used with compatible housing



### PRODUCT IMAGES AND DIMENSIONS



## 5" BR/PAR30 Eyeball with Metal Trim

Catalog No. \_\_\_\_\_

**NT-5070W** = White BR/PAR30 Eyeball with White Metal Trim

## Compatible Housings

Catalog No. \_\_\_\_\_

- NHIC-501QAT** = 5" IC Air-Tight New Construction Housing / 75W max
- NHRIC-504QAT** = 5" IC Air-Tight Remodel Housing / 75W max
- NHIC-527QAT** = 5" Shallow IC Air-Tight New Construction Housing / 50W max
- NHRIC-527QAT** = 5" Shallow IC Air-Tight Remodel Housing / 50W max
- NFBIC-5INCATA** = 5" Line Voltage IC Air-Tight Fire Rated Housing / 75W max

Example: **NT-5070W** = White BR/PAR30 Eyeball with White Metal Trim