

# NTS-5026

## 5" Front Loading Frosted Flat Lens with Specular Clear Reflector

Type \_\_\_\_\_

Project \_\_\_\_\_

Catalog No. \_\_\_\_\_

Notes \_\_\_\_\_

### FEATURES

**Trim:** Precision spun 0.050 aluminum high grade specular clear reflector with high grade frosted flat lens attached to trim. Easy lift and turn lens removal for re-lamping. Reflector includes two socket positions for optimum light control and output.  
Note: Shallow housings must use lowest socket position.

**Mounting:** Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86).

### COMPATIBLE HOUSINGS

Compatible with Line Voltage housings. See individual specification sheets for more information.

### LAMP

25W A19 Maximum (NHIC-501QAT; NHRIC-504QAT)

35W PAR30 Maximum (NHIC-501QAT; NHIC-527QAT; NHRIC-504QAT; NHRIC-527QAT)

60W A19 Maximum (NH-501Q; NHR-504Q)

### LABELS AND LISTINGS

· cULus Listed for Wet Location when used with compatible housing



### PRODUCT IMAGES AND DIMENSIONS



### 5" Front Loading Frosted Flat Lens with Specular Clear Reflector and Trim

Catalog No. \_\_\_\_\_

**NTS-5026W** = 5" Front Loading Frosted Flat Lens with Specular Clear Reflector and White Trim

### Compatible Housings

Catalog No. \_\_\_\_\_

**NH-5010** = 5" Non-IC New Construction Housing / 60W max

**NHR-5040** = 5" Non-IC Remodel Housing / 60W max

**NHIC-501QAT** = 5" IC Air-Tight New Construction Housing / 35W max

**NHRIC-504QAT** = 5" IC Air-Tight Remodel Housing / 35W max

**NHIC-527QAT** = 5" IC Shallow Air-Tight New Construction Housing / 35W max

**NHRIC-527QAT** = 5" IC Shallow Air-Tight Remodel Housing / 35W max

Example: **NTS-5026W** = 5" Front Loading Frosted Flat Lens with Specular Clear Reflector and White Trim