

# NT-25

## 6" Half Moon Wall Wash with Reflector

Type \_\_\_\_\_

Project \_\_\_\_\_

Catalog No. \_\_\_\_\_

Notes \_\_\_\_\_

### FEATURES

**Trim:** High grade albalite lens attached to metal trim. Lens can be easily removed by hand without tools from below the ceiling for relamping

**Mounting:** Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86).

### COMPATIBLE HOUSINGS

Compatible with line voltage housings. See individual specification sheets for more information.

### LAMP

Line Voltage

40W A19 Maximum (NHIC-170AT; NHIC-270AT; NHRIC-170AT; NHRIC-270AT)

60W A19 Maximum (NH-260; NHIC-17/100DWQA; NH-270; NHR-260; NHR-270)

Sloped Line Voltage


40W A19 Maximum (NHIC-926/DWQAT; NHIC-926QAT; NHRIC-926QAT)

### LABELS AND LISTINGS

- cULus Listed for Damp Location when used with compatible housing.



### PRODUCT IMAGES AND DIMENSIONS



### 6" Half Moon Wall Wash with Reflector

Catalog No.

**NT-25** = White Half Moon Wall Wash with White Reflector and White Metal Trim

### Compatible Housings

Catalog No.

- NH-260** = Non-IC New Construction / 60W max
- NHR-260** = Non-IC Remodel / 60W max
- NH-270** = Non-IC New Construction / 60W max
- NHR-270** = Non-IC Remodel / 60W max
- NHIC-17/100DWQA** = IC Air-Tight Double Wall New Construction / 60W max
- NHIC-17AT** = IC Air-Tight New Construction / 40W max
- NHIC-270AT** = IC Air-Tight New Construction / 40W max
- NHRIC-170AT** = IC Air-Tight New Construction / 40W max
- NHRIC-270AT** = IC Air-Tight New Construction / 40W max
- NHIC-926/DWQAT** = IC Air-Tight New Construction / 75W max
- NHIC-926QAT** = IC Air-Tight New Construction / 75W max
- NHRIC-926QAT** = IC Air-Tight New Construction / 75W max

Example: **NT-25** = White Half Moon Wall Wash with White Reflector and White Metal Trim