

NT-5021

5" Reflector Cone with Metal Ring

Type _____

Project _____

Catalog No. _____

Notes _____

FEATURES

Trim: Precision spun 0.050 high grade aluminum reflector and metal trim ring may also be used with custom combination of ring finishes.

Mounting: Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86). Remove socket from socket plate within housing (if applicable), and mount socket onto bracket.

COMPATIBLE HOUSINGS

Compatible with Line Voltage housings. See individual specification sheets for more information.

LAMP

60W A19 (NFBIC-5INCATA)


40W A19 (NHIC-501QAT; NHRIC-504QAT)

LABELS AND LISTINGS

cULus Listed for Damp Locations when used with compatible housing



PRODUCT IMAGES AND DIMENSIONS



5" Specular Reflector with White Metal Ring

Catalog No. _____

NT-5021C = Specular Clear Reflector with White Metal Ring

Compatible Housings

Catalog No. _____

NHIC-501QAT = 5" IC Air-Tight New Construction / 40W max

NHRIC-504QAT = 5" IC Air-Tight Remodel / 40W max

NFBIC-5INCATA = 5" IC Air-Tight Fire Rated New Construction / 60W max

Example: **NT-5021C** = Specular Clear Reflector with White Metal Ring