

# NT-5061

## 5" Stepped Baffle with Adjustable Gimbal

Type \_\_\_\_\_

Project \_\_\_\_\_

Catalog No. \_\_\_\_\_

Notes \_\_\_\_\_

### FEATURES

**Trim:** Precision spun 0.040 baffle with deep grooves to reduce aperture glare. Trim with gimbal ring can be adjusted up to 30°.

**Mounting:** Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86). Remove socket from socket plate within housing (if applicable), and mount directly onto trim.

### COMPATIBLE HOUSINGS

Compatible with Line Voltage housings. See individual specification sheets for more information.

### LAMP


75W PAR30 Maximum (NHIC-501QAT; NHRIC-504QAT)

### LABELS AND LISTINGS

cULus Listed for Damp Locations when used with compatible housing



### PRODUCT IMAGES AND DIMENSIONS



4-5/8"  
6-1/2"

## 5" PAR30 Stepped Baffle with Adjustable Gimbal

Catalog No. \_\_\_\_\_

**NT-5061W** = White Stepped Baffle with White Adjustable Gimbal and White Flange

## Compatible Housings

Catalog No. \_\_\_\_\_

**NHIC-501QAT** = 5" IC Air-Tight New Construction Housing / 75W max

**NHRIC-504QAT** = 5" IC Air-Tight Remodel Housing / 75W max

Example: **NT-5061W** = White Stepped Baffle with White Adjustable Gimbal and White Flange