SATCO® | NUVO®

Project/Job Name:

Location:

Fixture Type:

Notes:

65-632R1 - LED Canopy Fixture; 100 Watt; CCT Selectable; Bronze Finish

- CCT Selectable
- Has Driver

UL CERTIFIED · RoHS COMPLIANT · FC · DIMMABLE · WET LOCATION · DLC LISTED PREMIUM

ELECTRICAL

Technology:	LED
Watts:	100W
Volts:	120V-277V
Lumens:	14298L/15322/14943L
CRI:	80
CCT (Kelvins):	3000K/4000K/5000K
Color Description:	Warm to Cool White
Beam Spread :	150
Hours Rated:	50000
Dimmable:	Yes-Dimmable
DimmableText:	0-10V Dimming
Operating Temperature :	-40C (-40F) to +45C (+113F)
Number of LEDs :	240
Surge Protection :	Built-in surge protection - 6KV
THD:	<20%
Power Factor :	>0.9
Voltage Type:	Range Voltage
Warranty:	5 Year Limited - Fixtures

PACKAGING

Each UPC:	045923652851
Each Quantity:	1
Each Dimensions:	12.80 x 12.80 x 5.51
Case UPC:	10045923652858
Case Quantity:	2
Case Dimensions:	13.58 x 11.81 x 13.58

PHYSICAL

Finish:	Bronze
Lens Material:	Polycarbonate (PC)
Finish Family:	Bronze
Dimensions:	H:3.15" DIA:11.02"
Weight (Lbs.):	6.56
Material:	Die-cast Aluminum
Sensor:	Optional Add-On

COMPLIANCE

Safety Listing:	cULus - Listed
Location Rating:	Wet
Indoor/Outoor:	Outdoor
Energy Star Qualified:	No
DLC Approved:	Yes
DLC Classification:	Premium
DLC ID:	S-ZW3LNP
DLC Primary Use:	Parking Garage Luminaires
CA Prop 65:	Lead
BAA Compliant:	No
FCC Compliant:	Yes
IP Rating:	IP65
IK Rating:	IK10
RoHS Compliant:	Yes
SDS Class:	LED_Fixture
B.U.G Rating:	B3-U3-G2
Restrictions:	No Restrictions

INFO

Specification Note:	UV Stabilized Powder Coated Finish

ACCESSORIES

	65-639	Add on Emergency Backup Battery for LED Round Canopy Light Fixtures; 15 Watt; 90 min. Run Time; Black Finish
	86-217	Add-On PIR Sensor; 6 Meter
	86-218	Add-On Microwave Sensor; 12 Meter
	86-219	Programing Remote Control for use with 86-218, 86-217 & 86-220 Sensors
	86-220	Add-On PIR Sensor; 12 Meter

DIMMER COMPATIBILITY

LeGrand	ADPD4FBL3P2W4
Eaton	DF10P
Leviton	DS710-10Z
Lutron	DVSCSTV
Lutron	DVSTV
Lutron	MS-Z101
Lutron	MS-Z101-V
Lutron	NTSTV-DV
Eaton	SF10P