



ELECTRICAL

ELECTRICAL	
Technology:	LED
Watts:	20W
Volts:	120V-347V
Lumens:	2164L-2505L
Lamp Base :	Integrated
Lamp Shape :	Integrated LED
CRI:	80
CCT (Kelvins):	3000K/4000K/5000K
Temperature:	Warm to Cool White
Beam Spread :	120
Hours Rated:	50000
Dimmable:	Yes-Dimmable
Dimmable Down To %:	100 to 20 percent
DimmableText:	0-10V Dimming
Incandescent Equivalent :	125W
HID Equivalent :	50W
Operating Temperature :	-40C (-40F) to +45C (+113F)
Lamp Included :	Integrated
Replaceable Light Source :	No
Surge Protection :	Built-in surge protection - 2KV
THD:	10.30%
Power Factor :	>0.96
Warranty:	5 Year Limited - Fixtures

PACKAGING

Each UPC:	045923650956
Each Quantity:	1
Each Dimensions:	25.98 x 5.71 x 3.94
Case UPC:	10045923650953
Case Quantity:	6
Case Dimensions:	25.98 x 11.42 x 11.81

Project/Job Name:

Location:

Fixture Type:

Notes:

65-820R1 - 2 Foot; 20 Watt; Vapor Proof Linear Fixture; CCT Selectable; IP65 and IK08 Rated; 0-10V Dimming; 120V-347V

• CCT Selectable

• Has Driver













PHYSICAL

Finish:	Gray
Lens Material:	Polycarbonate (PC)
Finish Family:	Gray
Dimensions:	L:23.62" W:4.92" H:3.46"
Weight (Lbs.):	3.09
Material:	Plastic

COMPLIANCE

Safety Listing:	cETLus - Listed
Location Rating:	Wet
Indoor/Outoor:	Indoor and Outdoor
Energy Star Qualified:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-L9WQOF
DLC Primary Use:	Direct Linear Ambient
	Luminaires
CA Prop 65:	Lead
Vapor Tight Fixture Rated:	Yes
FCC Compliant:	Yes
IP Rating:	IP65
IK Rating:	IKo8
NSF Approved:	Yes
RoHS Compliant:	Yes
SDS Class:	LED_Fixture
Restrictions:	No Restrictions